

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 294(E) CSD (Aerosol)

Revision date: 28.07.2017

Page 1 of 14

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

294(E) CSD (Aerosol)

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Fast evaporating solvent degreaser. Do not use on oxygen systems.

###### Uses advised against

No information available.

##### 1.3. Details of the supplier of the safety data sheet

Company name:	Chesterton International GmbH	
Street:	Am Lenzenfleck 23	
Place:	DE-85737 Ismaning GERMANY	
Telephone:	+49 89 99 65 46 - 0	Telefax: +49 89 99 65 46 - 50
e-mail:	eu-sds@chesterton.com	
e-mail (Contact person):	eu-sds@chesterton.com	
Internet:	www.chesterton.com	
Responsible Department:	eu-sds@chesterton.com	

##### 1.4. Emergency telephone number:

+49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Regulation (EC) No. 1272/2008

Hazard categories:

Aerosol: Aerosol 1

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

##### 2.2. Label elements

###### Regulation (EC) No. 1272/2008

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 294(E) CSD (Aerosol)

Revision date: 28.07.2017

Page 2 of 14

#### Hazard components for labelling

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane acetone

Propan-2-ol

(R)-p-mentha-1,8-diene, d-limonene

**Signal word:** Danger

#### Pictograms:



#### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

#### Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe vapour/aerosol.
P280	Wear protective gloves and eye/face protection.
P312	Call a POISON CENTER/doctor if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 294(E) CSD (Aerosol)

Revision date: 28.07.2017

Page 3 of 14

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			50-100 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
67-64-1	acetone			15-25 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
67-63-0	Propan-2-ol			2,5-10 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
5989-27-5	(R)-p-mentha-1,8-diene, d-limonene			2,5-10 %
	227-813-5	601-029-00-7	01-2119529223-47	
	Flam. Liq. 3, Skin Irrit. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H226 H315 H317 H400 H410			
124-38-9	Carbon dioxide			2,5-10 %
	204-696-9			
	Compressed gas; H280			

Full text of H and EUH statements: see section 16.

#### Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons, perfumes (Limonene).

#### Further Information

No information available.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

Change contaminated, saturated clothing. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

##### After inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Call a doctor.

##### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 294(E) CSD (Aerosol)

Revision date: 28.07.2017

Page 4 of 14

#### **After contact with eyes**

Rinse immediately carefully and thoroughly with eye-bath or water. If eye irritation persists: Get medical advice/attention.

#### **After ingestion**

Do NOT induce vomiting.  
Immediately call a doctor.

#### **4.2. Most important symptoms and effects, both acute and delayed**

No information available.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Dry extinguishing powder. Carbon dioxide (CO<sub>2</sub>). alcohol resistant foam. Water spray jet

##### **Unsuitable extinguishing media**

High power water jet

#### **5.2. Special hazards arising from the substance or mixture**

Heating causes rise in pressure with risk of bursting.  
Vapours can form explosive mixtures with air.

#### **5.3. Advice for firefighters**

Special protective equipment for firefighters Protective clothing.  
In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

See protective measures under point 7 and 8.  
Provide adequate ventilation.  
Personal protection equipment: see section 8

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Cover drains.

#### **6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### **6.4. Reference to other sections**

See protective measures under point 7 and 8.  
Disposal: see section 13

### **SECTION 7: Handling and storage**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 294(E) CSD (Aerosol)

Revision date: 28.07.2017

Page 5 of 14

#### 7.1. Precautions for safe handling

##### Advice on safe handling

See section 8. Wear personal protection equipment (refer to section 8).

##### Advice on protection against fire and explosion

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

##### Further information on handling

Do not pierce or burn, even after use.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep cool. Protect from sunlight.

Pressurised container: May burst if heated.

##### Further information on storage conditions

Keep away from:

Frost

Heat

Humidity

#### 7.3. Specific end use(s)

No information available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 294(E) CSD (Aerosol)

Revision date: 28.07.2017

Page 6 of 14

#### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
67-64-1	acetone			
Worker DNEL, long-term		inhalation	systemic	1210 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	2420 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	186 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	200 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	62 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	62 mg/kg bw/day
67-63-0	Propan-2-ol			
Worker DNEL, long-term		inhalation	systemic	500 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	89 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
5989-27-5	(R)-p-mentha-1,8-diene, d-limonene			
Worker DNEL, long-term		inhalation	systemic	66,7 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	9,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	16,6 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	4,8 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	4,8 mg/kg bw/day

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 294(E) CSD (Aerosol)

Revision date: 28.07.2017

Page 7 of 14

#### PNEC values

CAS No	Substance	
Environmental compartment		Value
67-64-1	acetone	
Freshwater		10,6 mg/l
Marine water		1,06 mg/l
Freshwater sediment		30,4 mg/l
Marine sediment		3,04 mg/l
Soil		29,5 mg/l
67-63-0	Propan-2-ol	
Freshwater		140,9 mg/l
Freshwater (intermittent releases)		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Secondary poisoning		160 mg/kg
Micro-organisms in sewage treatment plants (STP)		2251 mg/l
Soil		28 mg/kg
5989-27-5	(R)-p-mentha-1,8-diene, d-limonene	
Freshwater		0,014 mg/l
Marine water		0,0014 mg/l
Freshwater sediment		3,85 mg/kg
Marine sediment		0,385 mg/kg
Secondary poisoning		133 mg/kg
Soil		0,763 mg/kg

#### 8.2. Exposure controls

##### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

##### Protective and hygiene measures

Work in well-ventilated zones or use proper respiratory protection. Only wear fitting, comfortable and clean protective clothing. Avoid contact with skin, eyes and clothes. Wash hands and face before breaks and after work and take a shower if necessary.

##### Eye/face protection

Suitable eye protection:  
 Eye glasses with side protection  
 goggles

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 294(E) CSD (Aerosol)

Revision date: 28.07.2017

Page 8 of 14

#### Hand protection

Tested protective gloves must be worn: DIN EN 374  
 NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)  
 Thickness of the glove material  $\geq 0,4$  mm  
 Breakthrough times and swelling properties of the material must be taken into consideration.  
 For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.  
 Wearing time with occasional contact (splashes): max. 480 min. (NBR (Nitrile rubber))  
 Wearing time with permanent contact 240 - 480 min (NBR (Nitrile rubber))  
 Observe the wear time limits as specified by the manufacturer.

#### Skin protection

Protective clothing

#### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.  
 Filtering device (full mask or mouthpiece) with filter: AX

#### Environmental exposure controls

No special measures are necessary.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: liquid  
 Colour: colourless  
 Odour: like: Lemon

#### Test method

pH-Value: not applicable

#### Changes in the physical state

Melting point: not determined  
 Initial boiling point and boiling range: 56 °C  
 Sublimation point: not determined  
 Softening point: not determined  
 Pour point: not determined  
 Flash point: -18 °C

#### Flammability

Solid: not determined  
 Gas: not determined

#### Explosive properties

Vapours can form explosive mixtures with air.

Lower explosion limits: 1,1 vol. %



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 294(E) CSD (Aerosol)

Revision date: 28.07.2017

Page 9 of 14

Upper explosion limits:	7 vol. %
Ignition temperature:	222 °C
<b>Auto-ignition temperature</b>	
Solid:	not determined
Gas:	not determined
Decomposition temperature:	not determined
<b>Oxidizing properties</b>	
No information available.	
Vapour pressure: (at 20 °C)	not determined
Density (at 20 °C):	0,71 g/cm <sup>3</sup>
Water solubility:	practically insoluble
<b>Solubility in other solvents</b>	
No information available.	
Partition coefficient:	not determined
Viscosity / dynamic:	not determined
Vapour density:	>1 (air = 1)
Evaporation rate:	<1 (Ether = 1)
Solvent content:	100 Vol%

#### **9.2. Other information**

No information available.

### **SECTION 10: Stability and reactivity**

#### **10.1. Reactivity**

The product is stable under storage at normal ambient temperatures.

#### **10.2. Chemical stability**

The substance is chemically stable under recommended conditions of storage, use and temperature.

#### **10.3. Possibility of hazardous reactions**

This material is considered to be non-reactive under normal use conditions.

#### **10.4. Conditions to avoid**

This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

#### **10.5. Incompatible materials**

No information available.

#### **10.6. Hazardous decomposition products**

Nitrogen oxides (NOx), Carbon dioxide (CO<sub>2</sub>), Carbon monoxide

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 294(E) CSD (Aerosol)

Revision date: 28.07.2017

Page 10 of 14

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-64-1	acetone				
	oral	LD50 5800 mg/kg	Rat	RTECS	
	dermal	LD50 20000 mg/kg	Rabbit	IUCLID	
	inhalative (4 h) vapour	LC50 76 mg/l	Rat		
67-63-0	Propan-2-ol				
	oral	LD50 5045 mg/kg	Rat		
	dermal	LD50 12800-13400 mg/kg	Rabbit		
	inhalative (4 h) vapour	LC50 30-46,5 mg/l	Rat		
5989-27-5	(R)-p-mentha-1,8-diene, d-limonene				
	oral	LD50 > 2000 mg/kg	Rat	OECD Guideline 423	

#### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

#### Sensitising effects

May cause an allergic skin reaction. ((R)-p-mentha-1,8-diene, d-limonene)

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane; acetone)

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 294(E) CSD (Aerosol)

Revision date: 28.07.2017

Page 11 of 14

#### 12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-64-1	acetone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna	
67-63-0	Propan-2-ol					
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas	OECD Guideline 203
	Acute crustacea toxicity	EC50 mg/l	13299	48 h	Daphnia magna (Big water flea)	

#### 12.2. Persistence and degradability

No information available.

#### 12.3. Bioaccumulative potential

##### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone	-0,24

#### 12.4. Mobility in soil

No information available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

No information available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Advice on disposal

Dispose of waste according to applicable legislation.

##### Contaminated packaging

Dispose of waste according to applicable legislation.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 294(E) CSD (Aerosol)

Revision date: 28.07.2017

Page 12 of 14

**14.4. Packing group:** -  
 Hazard label: 2.1  
 Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Excepted quantity: E0  
 Transport category: 2  
 Tunnel restriction code: D

#### Inland waterways transport (ADN)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
 Hazard label: 2.1  
 Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Excepted quantity: E0

#### Marine transport (IMDG)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1  
 Special Provisions: 63, 190, 277, 327, 344, 381,959  
 Limited quantity: 1000 mL  
 Excepted quantity: E0  
 EmS: F-D, S-U

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1  
 Special Provisions: A145 A167 A802  
 Limited quantity Passenger: 30 kg G  
 Passenger LQ: Y203  
 Excepted quantity: E0  
 IATA-packing instructions - Passenger: 203  
 IATA-max. quantity - Passenger: 75 kg  
 IATA-packing instructions - Cargo: 203

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 294(E) CSD (Aerosol)

Revision date: 28.07.2017

Page 13 of 14

IATA-max. quantity - Cargo: 150 kg

#### **14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: yes  
Danger releasing substance: naphta

#### **14.6. Special precautions for user**

No information available.

#### **14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No information available.

### SECTION 15: Regulatory information

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### **National regulatory information**

Water contaminating class (D): 2 - water contaminating

#### **15.2. Chemical safety assessment**

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane  
acetone  
Propan-2-ol  
(R)-p-mentha-1,8-diene, d-limonene

### SECTION 16: Other information

#### **Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer  
(Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO: International Civil Aviation Organization  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
EC50: Effectice concentration, 50 percent  
DNEL: Derived No Effect Level  
PNEC: Predicted No Effect Concentration  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 294(E) CSD (Aerosol)

Revision date: 28.07.2017

Page 14 of 14

#### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 2; H411	Calculation method

#### Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Further Information

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself.  
 No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose.  
 The user must make their own determination as to suitability.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*