

725

Nickle Anti-Seize Compound

Thread Lubricant; Withstands Extreme Pressure and High Temperature

Chesterton 725 is a high performance, nickel-based anti-seize that combines the extreme pressure, corrosion-resistant, anti-seize abilities of colloidal nickel in an oil suspension that can withstand temperatures up to 1425°C (2597°F).

Product Characteristics

- Ultra-fine particles
- Guards against galling and corrosion
- Protects against self-welding
- Withstands extreme pressure
- Up to 1425°C (2597°F)

Applications

Covers all industries
Mechanical assembly of:

- Bolts
- Studs
- Flanges
- Press fits
- Valve stems
- Pump sleeves
- Screws
- Bushings
- Gaskets
- Bearings



- Lubricates for assembly and disassembly
- Protects against corrosion
- No need for torque tension recalculation

Container Size	Reorder Number
----------------	----------------

725

Aerosol	082351
250 Gram Brush Top	081266
500 Gram Brush Top	082359
20 Liter	082349

Physical Properties

Average Particle Size	4 to 7 microns
Temperature Range	Up to 1425°C (2600°F)
Coefficient of Friction "K" Factor Method Skidmore-Wilhelm Method	0.18

Chesterton ISO certificates available on
www.chesterton.com/corporate/iso

Distributed by:

Technical data reflects results of laboratory tests and is intended to indicate general characteristics only. A.W. Chesterton Company disclaims all warranties express or implied, including warranties of merchantability and fitness for a particular purpose. Liability, if any, is limited to product replacement only. Any images contained herein are for general illustrative or aesthetic purposes only and are not intended to convey any instructional, safety, handling or usage information or advice respecting any product or equipment. Please refer to relevant Safety Data Sheets, Product Data Sheets, and/or Product Labels for safe use, storage, handling, and disposal of products, or consult with your local Chesterton sales representative.

© 2018 A.W. Chesterton Company.
® Registered trademark owned by A.W. Chesterton Company
in USA and other countries, unless otherwise noted.



A.W. Chesterton Company
860 Salem Street
Groveland, MA 01834 USA

Telephone: 781-438-7000
Fax: 978-469-6528
www.chesterton.com

Form No. EN36548.08
725 PDS – English
02/18