

Safety Data Sheet

according to Regulation (EC) No 1907/2006

276(E) Electronic Component Cleaner (Aerosol)

Revision date: 22.07.2021

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

276(E) Electronic Component Cleaner (Aerosol)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Petroleum base cleaner

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name:	Chesterton International GmbH	
Street:	Am Lenzenfleck 23	
Place:	D-85737 Ismaning GERMANY	
Telephone:	+49 89 99 65 46 - 0	Telefax: +49 89 99 65 46 - 50
e-mail:	eu-sds@chesterton.com	
e-mail (Contact person):	eu-sds@chesterton.com	
Internet:	www.chesterton.com	
Responsible Department:	eu-sds@chesterton.com	

1.4. Emergency telephone number: +49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Hydrocarbons, C7-C9, isoalkanes

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

276(E) Electronic Component Cleaner (Aerosol)

Revision date: 22.07.2021

Page 2 of 13

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P273	Avoid release to the environment.
P391	Collect spillage.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
	Hydrocarbons, C7-C9, isoalkanes			85-95 %
	921-728-3		01-2119471305-42	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			5-9 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
124-38-9	Carbon dioxide			1-5 %
	204-696-9			
	Compressed gas; H280			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

276(E) Electronic Component Cleaner (Aerosol)

Revision date: 22.07.2021

Page 3 of 13

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
	921-728-3	Hydrocarbons, C7-C9, isoalkanes	85-95 %
		inhalation: LC50 = > 21 mg/l (vapours); dermal: LD50 = > 2200 - 2500 mg/kg; oral: LD50 = > 7100 - 7800 mg/kg	
67-63-0	200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	5-9 %
		inhalation: LC50 = 30 mg/l (vapours); dermal: LD50 = 12800-13400 mg/kg; oral: LD50 = 5045 mg/kg	

Further Information

No information available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Change contaminated, saturated clothing. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Call a doctor.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.
Immediately call a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Causes eye irritation. Causes skin irritation. Repeated exposure may cause skin dryness or cracking.
Most important symptoms and effects, both acute and delayed: Headache, Dizziness, Pulmonary oedema
Vapours may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Dry extinguishing powder. Carbon dioxide (CO₂). alcohol resistant foam. Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Heating causes rise in pressure with risk of bursting.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

276(E) Electronic Component Cleaner (Aerosol)

Revision date: 22.07.2021

Page 4 of 13

Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Special protective equipment for firefighters Protective clothing.
In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

See protective measures under point 7 and 8.
Provide adequate ventilation.
Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

See section 8. Wear personal protection equipment (refer to section 8).

Advice on protection against fire and explosion

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Wear protective gloves/protective clothing.

Further information on handling

Do not pierce or burn, even after use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep cool. Protect from sunlight.
Pressurised container: May burst if heated.

Hints on joint storage

Keep away from:
Food and feedingstuffs

Safety Data Sheet

according to Regulation (EC) No 1907/2006

276(E) Electronic Component Cleaner (Aerosol)

Revision date: 22.07.2021

Page 5 of 13

Further information on storage conditions

Keep away from:

Frost

Heat

Humidity

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
124-38-9	Carbon dioxide	5000	9000		TWA (8 h)	
		15000	27000		STEL (15 min)	
67-63-0	Propan-2-ol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L	Urine	End of shift at end of workweek

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
	Hydrocarbons, C7-C9, isoalkanes			
	Worker DNEL, long-term	inhalation	systemic	2035 mg/m ³
	Worker DNEL, long-term	dermal	systemic	773 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	608 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	699 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	699 mg/kg bw/day
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
	Worker DNEL, long-term	inhalation	systemic	500 mg/m ³
	Worker DNEL, long-term	dermal	systemic	888 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	89 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	319 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	26 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

276(E) Electronic Component Cleaner (Aerosol)

Revision date: 22.07.2021

Page 6 of 13

PNEC values

CAS No	Substance	
	Environmental compartment	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
	Freshwater	140,9 mg/l
	Freshwater (intermittent releases)	140,9 mg/l
	Marine water	140,9 mg/l
	Freshwater sediment	552 mg/kg
	Marine sediment	552 mg/kg
	Secondary poisoning	160 mg/kg
	Micro-organisms in sewage treatment plants (STP)	2251 mg/l
	Soil	28 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection:

Eye glasses with side protection
goggles

Hand protection

Tested protective gloves must be worn: EN ISO 374

NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)

Thickness of the glove material $\geq 0,4$ mm

Breakthrough times and swelling properties of the material must be taken into consideration.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Wearing time with occasional contact (splashes): max. 480 min. (NBR (Nitrile rubber))

Wearing time with permanent contact 240 - 480 min (NBR (Nitrile rubber))

Observe the wear time limits as specified by the manufacturer.

Skin protection

Protective clothing

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Filtering device (full mask or mouthpiece) with filter: A-P2

Environmental exposure controls

No special measures are necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:

Liquid

Safety Data Sheet

according to Regulation (EC) No 1907/2006

276(E) Electronic Component Cleaner (Aerosol)

Revision date: 22.07.2021

Page 7 of 13

Colour: clear
Odour: like: Petroleum

Changes in the physical state

Melting point/freezing point: not determined
Boiling point or initial boiling point and boiling range: 98 °C
Sublimation point: not determined
Softening point: not determined
Pour point: not determined
Flash point: -6,1 °C

Flammability

Solid/liquid: not determined
Gas: not determined

Explosive properties

Vapours can form explosive mixtures with air.

Lower explosion limits: not determined
Upper explosion limits: not determined
Auto-ignition temperature: ~382 °C

Self-ignition temperature

Solid: not determined
Gas: not determined

Decomposition temperature: not determined

Oxidizing properties

No information available.

Viscosity / kinematic:
(at 25 °C) 1 mm²/s

Water solubility: slightly soluble

Solubility in other solvents

No information available.

Partition coefficient n-octanol/water: <1

Vapour pressure:
(at 20 °C) ~80 hPa

Density (at 20 °C): 0,7 g/cm³

Relative vapour density: not determined

9.2. Other information

Sustaining combustion: Not sustaining combustion

Evaporation rate: not determined

Further Information

No information available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

276(E) Electronic Component Cleaner (Aerosol)

Revision date: 22.07.2021

Page 8 of 13

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The substance is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

This material is considered to be non-reactive under normal use conditions.

10.4. Conditions to avoid

This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

10.5. Incompatible materials

Strong acid, Strong alkali, Oxidising agent

10.6. Hazardous decomposition products

Nitrogen oxides (NO_x), Carbon dioxide (CO₂), Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C7-C9, isoalkanes				
	oral	LD50 > 7100 - 7800 mg/kg	Rat	Study report (1961)	OECD Guideline 401
	dermal	LD50 > 2200 - 2500 mg/kg	Rabbit	Study report (1961)	Standard acute method, applying 4 differ
	inhalation (4 h) vapour	LC50 > 21 mg/l	Rat	Study report (1985)	OECD Guideline 403
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 5045 mg/kg	Rat		
	dermal	LD50 12800-13400 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 30 mg/l	Rat		

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Safety Data Sheet

according to Regulation (EC) No 1907/2006

276(E) Electronic Component Cleaner (Aerosol)

Revision date: 22.07.2021

Page 9 of 13

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C7-C9, isoalkanes)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name						
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method	
	Hydrocarbons, C7-C9, isoalkanes						
	Acute fish toxicity	LL50 mg/l	18,4	96 h	Oncorhynchus mykiss	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50	12 mg/l	72 h	Pseudokirchneriella subcapitata	SIDS Initial Assessment Report For SIAM	OECD Guideline 201
	Acute crustacea toxicity	EL50 mg/l	ca. 2,4	48 h	Daphnia magna	REACH Registration Dossier	other: As described in: The evaluation o
	Fish toxicity	NOEC mg/l	0,778	28 d	Oncorhynchus mykiss	REACH Registration Dossier	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol						
	Acute fish toxicity	LC50 mg/l	10000	96 h	Pimephales promelas	Publication (1983)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	>100	72 h	Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 mg/l	13299	48 h	Daphnia magna (Big water flea)		

12.2. Persistence and degradability

No information available.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
	OECD 301E	95%	21	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

276(E) Electronic Component Cleaner (Aerosol)

Revision date: 22.07.2021

Page 10 of 13

12.3. Bioaccumulative potential

No information available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
	Hydrocarbons, C7-C9, isoalkanes	ca. 3,52
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05

BCF

CAS No	Chemical name	BCF	Species	Source
	Hydrocarbons, C7-C9, isoalkanes	ca. 105		REACH Registration D
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	<100		

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D

Inland waterways transport (ADN)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

276(E) Electronic Component Cleaner (Aerosol)

Revision date: 22.07.2021

Page 11 of 13

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1
Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1
Special Provisions: 63, 190, 277, 327, 344, 959
Limited quantity: 1000 mL
Excepted quantity: E0
EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1
Special Provisions: A145 A167 A802
Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0
IATA-packing instructions - Passenger: 203
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes
Danger releasing substance: Hydrocarbons, C7-C9, isoalkanes

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety Data Sheet

according to Regulation (EC) No 1907/2006

276(E) Electronic Component Cleaner (Aerosol)

Revision date: 22.07.2021

Page 12 of 13

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

2010/75/EU (VOC): 700 g/l

Information according to 2012/18/EU (SEVESO III): E2 Hazardous to the Aquatic Environment

Additional information: P3b

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C7-C9, isoalkanes

propan-2-ol; isopropyl alcohol; isopropanol

Carbon dioxide

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

EC50: Effectice concentration, 50 percent

DNEL: Derived No Effect Level

PNEC: Predicted No Effect Concentration

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 2; H411	Calculation method

Safety Data Sheet

according to Regulation (EC) No 1907/2006

276(E) Electronic Component Cleaner (Aerosol)

Revision date: 22.07.2021

Page 13 of 13

Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)