

Safety Data Sheet

according to Regulation (EC) No 1907/2006

706(E) Rustsolvo[®]

Revision date: 03.02.2023

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

706(E) Rustsolvo[®]

UFI: E3GV-8FUU-NNC4-8455

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Penetrating oil – frees nuts, bolts, fittings without injury to base metal.

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name: Chesterton International GmbH

Street: Am Lenzenfleck 23

Place: D-85737 Ismaning GERMANY

Telephone: +49 89 99 65 46 - 0

Telefax: +49 89 99 65 46 - 50

e-mail: eu-sds@chesterton.com

e-mail (Contact person): eu-sds@chesterton.com

Internet: www.chesterton.com

Responsible Department: eu-sds@chesterton.com

1.4. Emergency telephone

+49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 3; H226

Asp. Tox. 1; H304

STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics

Signal word: Danger

Pictograms:



Safety Data Sheet

according to Regulation (EC) No 1907/2006

706(E) Rustsolvo®

Revision date: 03.02.2023

Page 2 of 12

Hazard statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics			40 - < 45 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-48-9	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics	40 - < 45 %
	inhalation: LC50 = > 4,96 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		

Further Information

No information available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Change contaminated, saturated clothing. In case of accident or unwellness, seek medical advice immediately

Safety Data Sheet

according to Regulation (EC) No 1907/2006

706(E) Rustsolvo®

Revision date: 03.02.2023

Page 3 of 12

(show directions for use or safety data sheet if possible).

After inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Call a doctor.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Remove contaminated, saturated clothing immediately. In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Let 1 glass of water be drunken in little sips (dilution effect).

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Causes eye irritation. Causes skin irritation. Repeated exposure may cause skin dryness or cracking. Most important symptoms and effects, both acute and delayed: Headache, Dizziness, Pulmonary oedema. Vapours may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

- alcohol resistant foam
- Water spray jet
- Carbon dioxide (CO₂)
- Dry extinguishing powder

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Heating causes rise in pressure with risk of bursting.
Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Special protective equipment for firefighters Protective clothing.
In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

706(E) Rustsolvo®

Revision date: 03.02.2023

Page 4 of 12

In case of fire: Wear self-contained breathing apparatus.

Special protective equipment for firefighters: Protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

- Remove persons to safety.
- Provide adequate ventilation.
- Clear spills immediately.
- Avoid contact with skin, eyes and clothes.
- Safe handling: see section 7
- Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

See section 8. Wear personal protection equipment (refer to section 8).

Advice on protection against fire and explosion

- Vapours are heavier than air, spread along floors and form explosive mixtures with air.
- Take precautionary measures against static discharges.
- Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Advice on general occupational hygiene

Avoid contact with skin, eyes and clothes. Use protective skin cream before handling the product. Remove contaminated, saturated clothing immediately. When using do not eat, drink, smoke, sniff. Wash hands and face before breaks and after work and take a shower if necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep/Store only in original container.

Protect from direct sunlight.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

706(E) Rustsolvo®

Revision date: 03.02.2023

Page 5 of 12

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Keep away from:

- Frost
- Heat
- Humidity

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics			
	Worker DNEL, long-term	inhalation	systemic	871 mg/m ³
	Worker DNEL, long-term	dermal	systemic	77 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	185 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	46 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	46 mg/kg bw/day
	Worker DNEL, acute	inhalation	systemic	1286,4 mg/m ³
	Worker DNEL, long-term	inhalation	local	837,5 mg/m ³
	Worker DNEL, acute	inhalation	local	1066,67 mg/m ³
	Consumer DNEL, acute	inhalation	systemic	1152 mg/m ³
	Consumer DNEL, long-term	inhalation	local	178,57 mg/m ³
	Consumer DNEL, acute	inhalation	local	640 mg/m ³

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Take action to prevent static discharges.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection:

- Eye glasses with side protection
- goggles

Safety Data Sheet

according to Regulation (EC) No 1907/2006

706(E) Rustsolvo®

Revision date: 03.02.2023

Page 6 of 12

Hand protection

Tested protective gloves must be worn: EN ISO 374
 NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)
 Thickness of the glove material $\geq 0,4$ mm
 Breakthrough times and swelling properties of the material must be taken into consideration.
 For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.
 Wearing time with occasional contact (splashes): max. 480 min. (NBR (Nitrile rubber))
 Wearing time with permanent contact 240 - 480 min (NBR (Nitrile rubber))
 Observe the wear time limits as specified by the manufacturer.

Skin protection

Protective clothing

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.
 Filtering device (full mask or mouthpiece) with filter: A-P2

Thermal hazards

No data available

Environmental exposure controls

No special measures are necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	blue; green
Odour:	like: Petroleum

Test method

Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	No data available
Flammability	
Solid/liquid:	No data available
Gas:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	53,3 °C
Decomposition temperature:	No data available
pH-Value:	not applicable
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

706(E) Rustsolvo®

Revision date: 03.02.2023

Page 7 of 12

Solubility in other solvents

No information available.

Partition coefficient n-octanol/water:

No data available

Vapour pressure:

No data available

(at 20 °C)

Density (at 20 °C):

0,9 g/cm³

Relative vapour density:

>1 (air = 1)

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours can form explosive mixtures with air.

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No information available.

Other safety characteristics

Evaporation rate:

<1 (Ether = 1)

Solvent content:

49,7%

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

Viscosity / dynamic:

No data available

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The substance is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

This material is considered to be non-reactive under normal use conditions.

10.4. Conditions to avoid

This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

10.5. Incompatible materials

- Strong acid,
- Strong alkali,
- Oxidising agent

Safety Data Sheet

according to Regulation (EC) No 1907/2006

706(E) Rustsolvo®

Revision date: 03.02.2023

Page 8 of 12

10.6. Hazardous decomposition products

- Nitrogen oxides (NOx),
- Carbon dioxide (CO₂),
- Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1988)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1989)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 > 4,96 mg/l	Rat	Study report (1992)	OECD Guideline 403

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

706(E) Rustsolvo®

Revision date: 03.02.2023

Page 9 of 12

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Danio rerio	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EL50 > 100 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
	Fish toxicity	NOEC 0,131 mg/l	28 d	Oncorhynchus mykiss	Company report (2010)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC > 10,2 mg/l	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics	>= 3,17

BCF

CAS No	Chemical name	BCF	Species	Source
64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics	>= 30,85	calculated	REACH Registration D

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Safety Data Sheet

according to Regulation (EC) No 1907/2006

706(E) Rustsolvo®

Revision date: 03.02.2023

Page 10 of 12

Disposal recommendations

Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Packing which cannot be properly cleaned must be disposed of.
Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (naphta)
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (naphta)
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601
Limited quantity:	5 L
Excepted quantity:	E1

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (naphta)
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Special Provisions:	223, 274, 955
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1993
--------------------------------------	---------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

706(E) Rustsolvo®

Revision date: 03.02.2023

Page 11 of 12

14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (naphta)
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Special Provisions:	A3
Limited quantity Passenger:	10 L
Passenger LQ:	Y344
Excepted quantity:	E1
IATA-packing instructions - Passenger:	355
IATA-max. quantity - Passenger:	60 L
IATA-packing instructions - Cargo:	366
IATA-max. quantity - Cargo:	220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 4,5,6,7,8,9,10,11,12,13,14,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

706(E) Rustsolvo®

Revision date: 03.02.2023

Page 12 of 12

IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 IATA-DGR: Dangerous Goods Refulations by the "International Air Transport Association" (IATA)
 ICAO: International Civil Aviation Organization
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 EC50: Effectice concentration, 50 percent
 DNEL: Derived No Effect Level
 PNEC: Predicted No Effect Concentration
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Asp. Tox. 1; H304	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H336 May cause drowsiness or dizziness.
 EUH066 Repeated exposure may cause skin dryness or cracking.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)