

Safety Data Sheet

according to Regulation (EC) No 1907/2006

725(E) Nickel Anti-Seize Compound (Bulk)

Revision date: 07.05.2021

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

725(E) Nickel Anti-Seize Compound (Bulk)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Petroleum base. Use on stainless steel, steel, iron, aluminum, copper, brass, titanium, etc. Do not use on oxygen systems.

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name:	Chesterton International GmbH	
Street:	Am Lenzenfleck 23	
Place:	D-85737 Ismaning GERMANY	
Telephone:	+49 89 99 65 46 - 0	Telefax: +49 89 99 65 46 - 50
e-mail:	eu-sds@chesterton.com	
e-mail (Contact person):	eu-sds@chesterton.com	
Internet:	www.chesterton.com	
Responsible Department:	eu-sds@chesterton.com	

1.4. Emergency telephone number:

+49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin Sens. 1; H317
Carc. 2; H351
STOT RE 1; H372
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements


Regulation (EC) No 1272/2008

Hazard components for labelling

nickel powder

Signal word: Danger

Pictograms:



Hazard statements

H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

725(E) Nickel Anti-Seize Compound (Bulk)

Revision date: 07.05.2021

Page 2 of 14

H372 Causes damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.
P264 Wash hands thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
7440-02-0	nickel powder			25 - < 30 %
	231-111-4	028-002-01-4	01-2119438727-29	
	Carc. 2, Skin Sens. 1, STOT RE 1, Aquatic Chronic 3; H351 H317 H372 H412			
64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics			1 - < 5 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
67-56-1	methanol			< 1 %
	200-659-6	603-001-00-X	01-2119392409-28	
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

725(E) Nickel Anti-Seize Compound (Bulk)

Revision date: 07.05.2021

Page 3 of 14

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
7440-02-0	231-111-4	nickel powder	25 - < 30 %
		oral: LD50 = > 9000 mg/kg	
64742-48-9	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics	1 - < 5 %
		inhalation: LC50 = > 4,96 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
67-56-1	200-659-6	methanol	< 1 %
		inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: LD50 = 15800 mg/kg; oral: LD50 = > 1187 - 2769 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse. In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Let 1 glass of water be drunken in little sips (dilution effect).
Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

- alcohol resistant foam
- Water spray jet
- Carbon dioxide (CO₂)
- Dry extinguishing powder

Unsuitable extinguishing media

Full water jet

Safety Data Sheet

according to Regulation (EC) No 1907/2006

725(E) Nickel Anti-Seize Compound (Bulk)

Revision date: 07.05.2021

Page 4 of 14

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated:

- Carbon monoxide
- Carbon dioxide
- Nitrogen oxides (NOx)

5.3. Advice for firefighters

Special protective equipment for firefighters: Protective clothing.

Co-ordinate fire-fighting measures to the fire surroundings.

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation.

Safe handling: see section 7

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains. Adverse environmental effects

6.3. Methods and material for containment and cleaning up

For containment

Take up mechanically. Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Personal protection equipment: see section 8

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

When using do not eat, drink or smoke.

Wash hands before breaks and after work. Used working clothes should not be worn outside the work area.

Street clothing should be stored separately from work clothing.

Never use pressure to empty container. Keep/Store only in original container.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Work in well-ventilated zones or use proper respiratory protection. Only wear fitting, comfortable and clean protective clothing. Avoid contact with skin, eyes and clothes. Wash hands and face before breaks and after work and take a shower if necessary.

Use protective skin cream before handling the product.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

725(E) Nickel Anti-Seize Compound (Bulk)

Revision date: 07.05.2021

Page 5 of 14

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Keep away from:

- Frost
- Heat
- Humidity

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
7429-90-5	Aluminium metal (Respirable Fraction)	-	1		TWA (8 h)	
7782-42-5	Graphite (all forms except fibres) (Respirable Fraction)	-	2		TWA (8 h)	
67-56-1	Methyl alcohol	200	260		TWA (8 h)	
7440-02-0	Nickel	-	0.5		TWA (8 h)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
7440-02-0	Nickel	Ni	3 µg/L	Urine	After several consecutive working shifts
67-56-1	Methanol	Methanol	15 mg/L	Urine	End of shift

Safety Data Sheet

according to Regulation (EC) No 1907/2006

725(E) Nickel Anti-Seize Compound (Bulk)

Revision date: 07.05.2021

Page 6 of 14

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
7440-02-0	nickel powder			
Worker DNEL, long-term		inhalation	systemic	0,05 mg/m ³
Worker DNEL, long-term		inhalation	local	0,05 mg/m ³
Worker DNEL, acute		inhalation	local	11,9 mg/m ³
Worker DNEL, long-term		dermal	local	0,035 mg/cm ²
Consumer DNEL, acute		inhalation	local	0,8 mg/m ³
Consumer DNEL, long-term		dermal	local	0,035 mg/cm ²
Consumer DNEL, long-term		oral	systemic	0,011 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	0,37 mg/kg bw/day
7429-90-5	aluminium powder (stabilised)			
Worker DNEL, long-term		inhalation	systemic	3,72 mg/m ³
Worker DNEL, long-term		inhalation	local	3,72 mg/m ³
Consumer DNEL, long-term		oral	systemic	7,9 mg/kg bw/day
7782-42-5	Graphite (anode)			
Worker DNEL, long-term		inhalation	systemic	1,2 mg/m ³
Worker DNEL, long-term		inhalation	local	1,2 mg/m ³
Consumer DNEL, long-term		inhalation	local	0,3 mg/m ³
Consumer DNEL, long-term		oral	systemic	813 mg/kg bw/day
64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics			
Worker DNEL, long-term		inhalation	systemic	871 mg/m ³
Worker DNEL, long-term		dermal	systemic	77 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	185 mg/m ³
Consumer DNEL, long-term		dermal	systemic	46 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	46 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	1286,4 mg/m ³
Worker DNEL, long-term		inhalation	local	837,5 mg/m ³
Worker DNEL, acute		inhalation	local	1066,67 mg/m ³
Consumer DNEL, acute		inhalation	systemic	1152 mg/m ³
Consumer DNEL, long-term		inhalation	local	178,57 mg/m ³
Consumer DNEL, acute		inhalation	local	640 mg/m ³
67-56-1	methanol			
Worker DNEL, long-term		inhalation	systemic	130 mg/m ³

Safety Data Sheet

according to Regulation (EC) No 1907/2006

725(E) Nickel Anti-Seize Compound (Bulk)

Revision date: 07.05.2021

Page 7 of 14

Worker DNEL, acute	inhalation	systemic	130 mg/m ³
Worker DNEL, long-term	inhalation	local	130 mg/m ³
Worker DNEL, acute	inhalation	local	130 mg/m ³
Worker DNEL, long-term	dermal	systemic	20 mg/kg bw/day
Worker DNEL, acute	dermal	systemic	20 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	26 mg/m ³
Consumer DNEL, acute	inhalation	systemic	26 mg/m ³
Consumer DNEL, long-term	inhalation	local	26 mg/m ³
Consumer DNEL, acute	inhalation	local	26 mg/m ³
Consumer DNEL, long-term	dermal	systemic	4 mg/kg bw/day
Consumer DNEL, acute	dermal	systemic	4 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	4 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	4 mg/kg bw/day

PNEC values

CAS No	Substance	Value
Environmental compartment		
7440-02-0	nickel powder	
Freshwater		0,0071 mg/l
Freshwater (intermittent releases)		0 mg/l
Marine water		0,0086 mg/l
Freshwater sediment		109 mg/kg
Marine sediment		109 mg/kg
Secondary poisoning		0,12 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,33 mg/l
Soil		29,9 mg/kg
7429-90-5	aluminium powder (stabilised)	
Freshwater		0,0749 mg/l
Micro-organisms in sewage treatment plants (STP)		20 mg/l

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection:

Eye glasses with side protection
goggles

Hand protection

Tested protective gloves must be worn: EN ISO 374
NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)
Thickness of the glove material $\geq 0,11$ mm

Safety Data Sheet

according to Regulation (EC) No 1907/2006

725(E) Nickel Anti-Seize Compound (Bulk)

Revision date: 07.05.2021

Page 8 of 14

Breakthrough times and swelling properties of the material must be taken into consideration.
For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.
Wearing time with occasional contact (splashes): max. 480 min. (NBR (Nitrile rubber))
Wearing time with permanent contact 240 - 480 min (NBR (Nitrile rubber))
Observe the wear time limits as specified by the manufacturer.

Skin protection

For the protection against direct skin contact, body protective clothing is essential (in addition to the usual working clothes).

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Combination filtering device A-P3
Self-contained respirator (breathing apparatus)

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Paste
Colour:	grey
Odour:	like: Petroleum

Test method

Changes in the physical state

Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	No data available
Flash point:	95 °C

Flammability

Solid/liquid:	No data available
Gas:	No data available

Explosive properties

not explosive according to EU A.14

Lower explosion limits:	not applicable
Upper explosion limits:	not applicable
Auto-ignition temperature:	> 350 °C

Self-ignition temperature

Solid:	No data available
Gas:	No data available

Decomposition temperature:	No data available
----------------------------	-------------------

pH-Value:	not applicable
-----------	----------------

Viscosity / dynamic: (at 23 °C)	~ 1000000 mPa·s
------------------------------------	-----------------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

725(E) Nickel Anti-Seize Compound (Bulk)

Revision date: 07.05.2021

Page 9 of 14

Water solubility:	practically insoluble
Solubility in other solvents	
No information available.	
Partition coefficient n-octanol/water:	<1
Vapour pressure:	No data available
Density:	1,29 g/cm ³
Relative vapour density:	>1 (Air=1)

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties
(Air=1)

Other safety characteristics

Evaporation rate: <1 (Ether=1)

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

Does not decompose when used for intended uses.

10.3. Possibility of hazardous reactions

Formation of explosive mixtures with: Acid
Formation of: Hydrogen

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Acid

10.6. Hazardous decomposition products

- Hydrogen
- Carbon monoxide
- Carbon dioxide (CO₂).
- Nitrogen oxides (NO_x)

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

725(E) Nickel Anti-Seize Compound (Bulk)

Revision date: 07.05.2021

Page 10 of 14

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7440-02-0	nickel powder				
	oral	LD50 > 9000 mg/kg	Rat	Study report (1983)	OECD Guideline 401
64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1988)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1989)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 > 4,96 mg/l	Rat	Study report (1992)	OECD Guideline 403
67-56-1	methanol				
	oral	LD50 > 1187 - 2769 mg/kg	Rat	Study report (1975)	Study performed according to internal co
	dermal	LD50 15800 mg/kg			
	inhalation (4 h) vapour	LC50 128,2 mg/l	Rat	Study report (1980)	Study performed according to internal co
	inhalation dust/mist	ATE 0,5 mg/l			

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (nickel powder)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (nickel powder)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure. (nickel powder)

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

SECTION 12: Ecological information

12.1. Toxicity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

725(E) Nickel Anti-Seize Compound (Bulk)

Revision date: 07.05.2021

Page 11 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
7440-02-0	nickel powder					
	Acute fish toxicity	LC50 mg/l	15,3	96 h	Oncorhynchus mykiss	Aquatic Toxicology 63 (2003) 65-82 (2003) other: not reported
	Acute algae toxicity	ErC50 mg/l	0,237	72 h	Ankistrodesmus falcatus	Publication (2009) OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,276	48 h	Ceriodaphnia dubia	Study report (2005) Test methods were in accordance with app
	Fish toxicity	NOEC mg/l	0,057	32 d	Pimephales promelas	Water Resources Research Institute. Kent other: ASTM 1980, E-729
	Algae toxicity	NOEC	0,6 mg/l	14 d	Anabaena cylindrica	Environ. Pollut. (Series A). 25(4):241-2 other: not reported
	Crustacea toxicity	NOEC	0,0053 - 0,0153 mg/l	7 d	Ceriodaphnia dubia	Environmental Toxicology and Chemistry, other: EPA/600/4-91/00 2
	Acute bacteria toxicity	(EC50	33 mg/l)	0,5 h	Activated sludge	Journal of Hazardous Materials. B139:332 ISO 8192
64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics					
	Acute fish toxicity	LL50	8,2 mg/l	96 h	Pimephales promelas	Study report (1995) other: EPA 66013-75-009
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Raphidocelis subcapitata	REACH Registration Dossier OECD Guideline 201
	Acute crustacea toxicity	EL50	4,5 mg/l	48 h	Daphnia magna	Study report (1995) OECD Guideline 202
	Fish toxicity	NOEC mg/l	0,131	28 d	Oncorhynchus mykiss	REACH Registration Dossier The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC mg/l	0,23	21 d	Daphnia magna	REACH Registration Dossier The aquatic toxicity was estimated by a
67-56-1	methanol					
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 mg/l	ca. 22000	96 h	Raphidocelis subcapitata	Ecotoxicology and Environmental Safety 7 OECD Guideline 201

Safety Data Sheet

according to Regulation (EC) No 1907/2006

725(E) Nickel Anti-Seize Compound (Bulk)

Revision date: 07.05.2021

Page 12 of 14

	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Fish toxicity	NOEC mg/l	446,7	28 d	Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR
	Crustacea toxicity	NOEC	208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi

12.2. Persistence and degradability

No information available.

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
67-56-1	methanol		99	30	

12.3. Bioaccumulative potential

No information available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics	>= 3,17
67-56-1	methanol	-0,77

BCF

CAS No	Chemical name	BCF	Species	Source
7440-02-0	nickel powder	45	other aquatic crustacea: Cambarus bartoni	Bull. Environ. Conta
64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics	>= 30,85	calculated	REACH Registration D
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Safety Data Sheet

according to Regulation (EC) No 1907/2006

725(E) Nickel Anti-Seize Compound (Bulk)

Revision date: 07.05.2021

Page 13 of 14

Disposal recommendations

Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 27, Entry 28, Entry 40, Entry 69, Entry 75

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water hazard class (D):

2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

nickel powder

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics

methanol

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,4,5,6,7,8,9,10,11,12,14,15.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

725(E) Nickel Anti-Seize Compound (Bulk)

Revision date: 07.05.2021

Page 14 of 14

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer
(Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
CAS: Chemical Abstracts Service (division of the American Chemical Society)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
EC50: Effectice concentration, 50 percent
DNEL: Derived No Effect Level
PNEC: Predicted No Effect Concentration
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method
Carc. 2; H351	Calculation method
STOT RE 1; H372	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)