

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 775(E) Moisture Shield (Aerosol)

Revision date: 23.10.2017

Page 1 of 12

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

775(E) Moisture Shield (Aerosol)

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Displaces moisture; deposits a clear, protective coating for metals in process, storage, transit, use. Easily removable. This is a solvent base coating.

###### Uses advised against

No information available.

##### 1.3. Details of the supplier of the safety data sheet

Company name:	Chesterton International GmbH	
Street:	Am Lenzenfleck 23	
Place:	DE-85737 Ismaning GERMANY	
Telephone:	+49 89 99 65 46 - 0	Telefax: +49 89 99 65 46 - 50
e-mail:	eu-sds@chesterton.com	
e-mail (Contact person):	eu-sds@chesterton.com	
Internet:	www.chesterton.com	
Responsible Department:	eu-sds@chesterton.com	

##### 1.4. Emergency telephone number:

+49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Regulation (EC) No. 1272/2008

Hazard categories:

Aerosol: Aerosol 1

Respiratory or skin sensitisation: Skin Sens. 1

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

May cause an allergic skin reaction.

##### 2.2. Label elements

###### Regulation (EC) No. 1272/2008

###### Hazard components for labelling

Benzenesulfonic acid, di-C10-18-alkyl derivs., barium salts

**Signal word:** Danger

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 775(E) Moisture Shield (Aerosol)

Revision date: 23.10.2017

Page 2 of 12

#### Pictograms:



#### Hazard statements

- H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H317 May cause an allergic skin reaction.

#### Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P321 Specific treatment (see ... on this label).  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	75-85 %
	926-141-6	
	01-2119456620-43	
	Flam. Liq. 3, Asp. Tox. 1; H226 H304	
68603-10-1	Hydrocarbon waxes, petroleum, oxidized, methyl esters, barium salts	5-7 %
	271-637-1	
	Acute Tox. 4, Acute Tox. 4; H332 H302	
93820-55-4	Benzenesulfonic acid, di-C10-18-alkyl derivs., barium salts	3-6 %
	298-635-3	
	01-2119967414-32	
	Skin Sens. 1; H317	
124-38-9	Carbon dioxide	1-5 %
	204-696-9	
	Compressed gas; H280	

Full text of H and EUH statements: see section 16.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 775(E) Moisture Shield (Aerosol)

Revision date: 23.10.2017

Page 3 of 12

#### Further Information

No information available.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

Change contaminated, saturated clothing. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

##### After inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Call a doctor.

##### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

##### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. If eye irritation persists: Get medical advice/attention.

##### After ingestion

Do NOT induce vomiting.  
Immediately call a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Causes eye irritation. Causes skin irritation. Repeated exposure may cause skin dryness or cracking.  
Most important symptoms and effects, both acute and delayed: Headache, Dizziness, Pulmonary oedema  
Vapours may cause drowsiness and dizziness.

#### 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Dry extinguishing powder. Carbon dioxide (CO<sub>2</sub>). alcohol resistant foam. Water spray jet

##### Unsuitable extinguishing media

High power water jet

#### 5.2. Special hazards arising from the substance or mixture

Heating causes rise in pressure with risk of bursting.  
Vapours can form explosive mixtures with air.

#### 5.3. Advice for firefighters

Special protective equipment for firefighters Protective clothing.  
In case of fire: Wear self-contained breathing apparatus.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 775(E) Moisture Shield (Aerosol)

Revision date: 23.10.2017

Page 4 of 12

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### SECTION 6: Accidental release measures

##### 6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.  
Provide adequate ventilation.  
Personal protection equipment: see section 8

##### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains.

##### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

##### 6.4. Reference to other sections

See protective measures under point 7 and 8.  
Disposal: see section 13

#### SECTION 7: Handling and storage

##### 7.1. Precautions for safe handling

###### Advice on safe handling

See section 8. Wear personal protection equipment (refer to section 8).

###### Advice on protection against fire and explosion

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.  
Vapours are heavier than air, spread along floors and form explosive mixtures with air.

###### Further information on handling

Do not pierce or burn, even after use.

##### 7.2. Conditions for safe storage, including any incompatibilities

###### Requirements for storage rooms and vessels

Keep cool. Protect from sunlight.  
Pressurised container: May burst if heated.

###### Further information on storage conditions

Keep away from:  
Frost  
Heat  
Humidity

##### 7.3. Specific end use(s)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 775(E) Moisture Shield (Aerosol)

Revision date: 23.10.2017

Page 5 of 12

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL

#### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
93820-55-4	Benzenesulfonic acid, di-C10-18-alkyl derivs., barium salts			
Worker DNEL, long-term		inhalation	systemic	11,75 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day
Worker DNEL, long-term		dermal	local	1,03 mg/cm <sup>2</sup>
Consumer DNEL, long-term		inhalation	systemic	2,9 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	1,667 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,513 mg/cm <sup>2</sup>
Consumer DNEL, long-term		oral	systemic	0,833 mg/kg bw/day

#### PNEC values

CAS No	Substance	Value
93820-55-4	Benzenesulfonic acid, di-C10-18-alkyl derivs., barium salts	
Freshwater		1 mg/l
Marine water		1 mg/l
Freshwater sediment		226000000 mg/kg
Marine sediment		226000000 mg/kg
Secondary poisoning		16667 mg/kg
Soil		271000000 mg/kg

### 8.2. Exposure controls

#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 775(E) Moisture Shield (Aerosol)

Revision date: 23.10.2017

Page 6 of 12

#### Protective and hygiene measures

Work in well-ventilated zones or use proper respiratory protection. Only wear fitting, comfortable and clean protective clothing. Avoid contact with skin, eyes and clothes. Wash hands and face before breaks and after work and take a shower if necessary.

#### Eye/face protection

Suitable eye protection:

Eye glasses with side protection  
goggles

#### Hand protection

Tested protective gloves must be worn: DIN EN 374

NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)

Thickness of the glove material  $\geq 0,4$  mm

Breakthrough times and swelling properties of the material must be taken into consideration.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Wearing time with occasional contact (splashes): max. 480 min. (NBR (Nitrile rubber))

Wearing time with permanent contact 240 - 480 min (NBR (Nitrile rubber))

Observe the wear time limits as specified by the manufacturer.

#### Skin protection

Protective clothing

#### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Filtering device (full mask or mouthpiece) with filter: AX

#### Environmental exposure controls

No special measures are necessary.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	light brown
Odour:	like: Petroleum

pH-Value:	not applicable	<b>Test method</b>
-----------	----------------	--------------------

#### Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	207 °C
Sublimation point:	not determined
Softening point:	not determined
Pour point:	not determined

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 775(E) Moisture Shield (Aerosol)

Revision date: 23.10.2017

Page 7 of 12

Flash point: 66 °C

#### Flammability

Solid: not determined

Gas: not determined

#### Explosive properties

Vapours can form explosive mixtures with air.

Lower explosion limits: not determined

Upper explosion limits: not determined

Ignition temperature: not determined

#### Auto-ignition temperature

Solid: not determined

Gas: not determined

Decomposition temperature: not determined

#### Oxidizing properties

No information available.

Vapour pressure: not determined

Density (at 20 °C): 0,8 g/cm<sup>3</sup>

Water solubility: practically insoluble

#### Solubility in other solvents

No information available.

Partition coefficient: not determined

Viscosity / dynamic: not determined

Vapour density: >1 (air = 1)

Evaporation rate: <1 (Ether = 1)

Solvent content: 82 %

#### 9.2. Other information

No information available.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

#### 10.2. Chemical stability

The substance is chemically stable under recommended conditions of storage, use and temperature.

#### 10.3. Possibility of hazardous reactions

This material is considered to be non-reactive under normal use conditions.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 775(E) Moisture Shield (Aerosol)

Revision date: 23.10.2017

Page 8 of 12

#### 10.4. Conditions to avoid

This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

#### 10.5. Incompatible materials

Oxidising agent, strong

#### 10.6. Hazardous decomposition products

Nitrogen oxides (NOx), Carbon dioxide (CO<sub>2</sub>), Carbon monoxide

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
68603-10-1	Hydrocarbon waxes, petroleum, oxidized, methyl esters, barium salts				
	oral	ATE 500 mg/kg			
	inhalative vapour	ATE 11 mg/l			
	inhalative aerosol	ATE 1,5 mg/l			
93820-55-4	Benzenesulfonic acid, di-C10-18-alkyl derivs., barium salts				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1989)	OECD Guideline 401
	dermal	LD50 > 4000 mg/kg	Rabbit	Study report (1986)	other: 40 CFR, Secti

##### Irritation and corrosivity

Based on available data, the classification criteria are not met.

##### Sensitising effects

May cause an allergic skin reaction. (Benzenesulfonic acid, di-C10-18-alkyl derivs., barium salts)

##### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

##### STOT-single exposure

Based on available data, the classification criteria are not met.

##### STOT-repeated exposure

Based on available data, the classification criteria are not met.

##### Aspiration hazard

Based on available data, the classification criteria are not met.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 775(E) Moisture Shield (Aerosol)

Revision date: 23.10.2017

Page 9 of 12

## SECTION 12: Ecological information

### 12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
93820-55-4	Benzenesulfonic acid, di-C10-18-alkyl derivs., barium salts					
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1994)	EPA OTS 797.1050
	Acute bacteria toxicity	(> 10000 mg/l)	3 h	activated sludge of a predominantly domestic sewage	Study report (1994)	OECD Guideline 209

### 12.2. Persistence and degradability

No information available.

### 12.3. Bioaccumulative potential

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
93820-55-4	Benzenesulfonic acid, di-C10-18-alkyl derivs., barium salts	30,97

### 12.4. Mobility in soil

No information available.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Advice on disposal

Dispose of waste according to applicable legislation.

#### Contaminated packaging

Dispose of waste according to applicable legislation.

## SECTION 14: Transport information

### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
<b>14.4. Packing group:</b>	-

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 775(E) Moisture Shield (Aerosol)

Revision date: 23.10.2017

Page 10 of 12

Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D

#### Inland waterways transport (ADN)

<b><u>14.1. UN number:</u></b>	UN 1950
<b><u>14.2. UN proper shipping name:</u></b>	AEROSOLS
<b><u>14.3. Transport hazard class(es):</u></b>	2
<b><u>14.4. Packing group:</u></b>	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0

#### Marine transport (IMDG)

<b><u>14.1. UN number:</u></b>	UN 1950
<b><u>14.2. UN proper shipping name:</u></b>	AEROSOLS
<b><u>14.3. Transport hazard class(es):</u></b>	2.1
<b><u>14.4. Packing group:</u></b>	-
Hazard label:	2.1
Special Provisions:	63, 190, 277, 327, 344, 381,959
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U

#### Air transport (ICAO-TI/IATA-DGR)

<b><u>14.1. UN number:</u></b>	UN 1950
<b><u>14.2. UN proper shipping name:</u></b>	AEROSOLS, flammable
<b><u>14.3. Transport hazard class(es):</u></b>	2.1
<b><u>14.4. Packing group:</u></b>	-
Hazard label:	2.1
Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 775(E) Moisture Shield (Aerosol)

Revision date: 23.10.2017

Page 11 of 12

#### **14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

#### **14.6. Special precautions for user**

No information available.

#### **14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No information available.

### **SECTION 15: Regulatory information**

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### **National regulatory information**

Water contaminating class (D): 2 - clearly water contaminating

#### **15.2. Chemical safety assessment**

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Benzenesulfonic acid, di-C10-18-alkyl derivs., barium salts

### **SECTION 16: Other information**

#### **Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

EC50: Effectice concentration, 50 percent

DNEL: Derived No Effect Level

PNEC: Predicted No Effect Concentration

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 775(E) Moisture Shield (Aerosol)

Revision date: 23.10.2017

Page 12 of 12

#### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Skin Sens. 1; H317	Calculation method

#### Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.

#### Further Information

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself.  
No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose.  
The user must make their own determination as to suitability.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*