

SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 / WHMIS 2015 / GHS

Revision date: 24 September 2020

Initial date of issue: 6 July 2007

SDS No. 207B-22b

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: 274 Industrial Degreaser (Bulk)

Product name: Distillates (petroleum), hydrotreated light

CAS No.: 64742-47-8

1.2. Relevant identified uses of the substance or mixture and uses advised against

Petroleum base cleaner.

1.3. Details of the supplier of the safety data sheet

Company:

A.W. CHESTERTON COMPANY
860 Salem Street
Groveland, MA 01834-1507, USA
Tel. +1 978-469-6446 Fax: +1 978-469-6785
(Mon. - Fri. 8:30 - 5:00 PM EST)
SDS requests: www.chesterton.com
E-mail (SDS questions): ProductMSDSs@chesterton.com
E-mail: customer.service@chesterton.com

Supplier:

Canada: A.W. Chesterton Company Ltd., 889 Fraser Drive,
Unit 105, Burlington, Ontario L7L 4X8 - Tel. 905-335-5055
EU: Chesterton International GmbH, Am Lenzenfleck 23,
D85737 Ismaning, Germany - Tel. +49-89-996-5460

1.4. Emergency telephone number

24 hours per day, 7 days per week
Call Infotrac: 1-800-535-5053
Outside N. America: +1 352-323-3500 (collect)
NSW Poisons Information Centre (Australia): 13 11 26

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

2.1.1. Classification according to 29 CFR 1910.1200 / WHMIS 2015 / GHS

Flam. Liq. 4, H227
Asp. Tox. 1, H304
Skin Irrit. 2, H315
STOT SE 3, H336
Aquatic Chronic 2, H411

2.1.2. Australian statement of hazardous nature

Hazardous according to criteria of Safe Work Australia.

2.1.3. Additional information

For full text of H-statements: see SECTIONS 2.2 and 16.

2.2. Label elements

Labelling according to 29 CFR 1910.1200 / WHMIS 2015 / GHS

Hazard pictograms:



Signal word:

Danger

Hazard statements:	H227	Combustible liquid.
	H304	May be fatal if swallowed and enters airways.
	H315	Causes skin irritation.
	H336	May cause drowsiness or dizziness.
	H411	Toxic to aquatic life with long lasting effects.
Precautionary statements:	P210	Keep away from flames and hot surfaces. – No smoking.
	P233	Keep container tightly closed.
	P261	Avoid breathing vapours/spray.
	P264	Wash hands thoroughly after handling.
	P271	Use only outdoors or in a well-ventilated area.
	P273	Avoid release to the environment.
	P280	Wear protective gloves.
	P301/310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
	P331	Do NOT induce vomiting.
	P302/352	IF ON SKIN: Wash with plenty of soap and water.
	P332/313	If skin irritation occurs: Get medical advice/attention.
	P304/340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P312	Call a POISON CENTER or doctor/physician if you feel unwell.
	P362/364	Take off contaminated clothing and wash it before reuse.
	P370/378	In case of fire: Use CO2, dry chemical, foam or water spray to extinguish.
	P391	Collect spillage.
	P403/235	Store in a well-ventilated place. Keep cool.
	P405	Store locked up.
	P501	Dispose of contents/container to an approved waste disposal plant.
Supplemental information:	None	

2.3. Other hazards

None known

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.1. Substances**

Hazardous Ingredients ¹	% Wt.	CAS No.
Distillates (petroleum), hydrotreated light	100	64742-47-8

¹ Classified according to: 29 CFR 1910.1200, 1915, 1916, 1917, Mass. Right-to-Know Law (ch. 40, M.G.L..O. 111F), California Proposition 65, WHMIS 2015, Safe Work Australia, GHS

SECTION 4: FIRST AID MEASURES**4.1. Description of first aid measures**

Inhalation:	Remove to fresh air. If not breathing, administer artificial respiration. Contact physician immediately.
Skin contact:	Wash skin with soap and water. Take off contaminated clothing and wash it before reuse. Contact physician if irritation persists.
Eye contact:	Flush eyes for at least 15 minutes with large amounts of water. Contact physician if irritation persists.
Ingestion:	Do not induce vomiting. Contact physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Aspiration into the lungs may cause chemical pneumonitis or pulmonary oedema. Inhalation of vapor concentrations in excess of 1000 ppm will cause eye and respiratory tract irritation, dizziness, headache and other central nervous system effects. Prolonged or repeated skin contact may defat the skin and cause skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: FIREFIGHTING MEASURES**5.1. Extinguishing media**

Suitable extinguishing media: Carbon dioxide, dry chemical, foam or water spray

Unsuitable extinguishing media: High volume water jet

5.2. Special hazards arising from the substance or mixture

None

5.3. Advice for firefighters

Cool exposed containers with water. Recommend Firefighters wear self-contained breathing apparatus.

Flammability Classification: –

HAZCHEM Emergency Action Code:

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Provide adequate ventilation. Utilize exposure controls and personal protection as specified in Section 8.

6.2. Environmental Precautions

Keep out of sewers, streams and waterways.

6.3. Methods and material for containment and cleaning up

Contain spill to a small area. Keep away from sources of ignition - No smoking. If removal of ignition sources is not possible, then flush material away with water. Pick up with absorbent material (sand, sawdust, clay, etc.) and place in a suitable container for disposal.

6.4. Reference to other sections

Refer to section 13 for disposal advice.

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling**

Keep container closed when not in use. Electrically ground and bond equipment during transfer operations. Vapors are heavier than air and will collect in low areas. Vapor accumulations could flash and/or explode if ignited. Use only outdoors or in a well-ventilated area. Avoid breathing vapours/spray. Utilize exposure controls and personal protection as specified in Section 8.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, dry area.

7.3. Specific end use(s)

No special precautions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limit values**

Ingredients	OSHA PEL ¹		ACGIH TLV ²		AUSTRALIA ES ³	
	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Distillates (petroleum), hydrotreated light	–	–	179*	1200*	–	–

*Based on the procedure described in appendix H, "Reciprocal calculation method for Certain Refined Hydrocarbon Solvent Vapor Mixtures" of the ACGIH TLVs® and BEIs®.

¹ United States Occupational Health & Safety Administration permissible exposure limits

² American Conference of Governmental Industrial Hygienists threshold limit values

³ Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003]

8.2. Exposure controls**8.2.1. Engineering measures**

Provide sufficient ventilation to keep the vapor concentrations below the exposure limits.

8.2.2. Individual protection measures

Respiratory protection: Not normally needed. If exposure limits are exceeded, use approved organic vapor respirator (e.g., EN filter type A).

Protective gloves: Chemical resistant gloves (e.g. Viton*, neoprene, nitrile). *DuPont's registered trademark.

Eye and face protection: Safety glasses

Other: Impervious clothing as necessary to prevent skin contact.

8.2.3. Environmental exposure controls

Refer to sections 6 and 12.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Physical state	low viscosity liquid	Odour	mild
Colour	clear	Odour threshold	
Initial boiling point	192-205°C (377.6-401°F)	Vapour pressure @ 20°C	< 1 mm Hg
Melting point	not determined	% Aromatics by weight	≤ 0.2%
% Volatile (by volume)	100%	pH	not applicable
Flash point	67°C (152.6°F)	Relative density	0.8 kg/l
Method	Tag Closed Cup	Weight per volume	6.67 lbs/gal
Viscosity	1.6 cSt @ 25°C	Partition coefficient: n-octanol/water	2.1-6.5 (log Kow)
Autoignition temperature	> 220°C (> 428°F)	Vapour density (air=1)	> 1
Decomposition temperature	no data available	Rate of evaporation (ether=1)	< 1
Upper/lower flammability or explosive limits	LEL: 0.8; UEL: 6	Solubility in water	insoluble
Flammability (solid, gas)	not applicable	Oxidising properties	not determined
Explosive properties	not determined		

9.2. Other information

None

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

Refer to sections 10.3 and 10.5.

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No dangerous reactions known under conditions of normal use.

10.4. Conditions to avoid

Open flames, heat, sparks and red hot surfaces.

10.5. Incompatible materials

Strong oxidizers like liquid Chlorine and concentrated Oxygen.

10.6. Hazardous decomposition products

Carbon Monoxide, aldehydes and other toxic fumes.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

Primary route of exposure under normal use: Inhalation, skin and eye contact. Personnel with pre-existing dermatitis are generally aggravated by exposure.

Acute toxicity -

Oral: Based on available data, the classification criteria are not met.

Substance	Test	Result
Distillates (petroleum), hydrotreated light	LD50, rat	> 5000 mg/kg

Dermal: Based on available data, the classification criteria are not met.

Substance	Test	Result
Distillates (petroleum), hydrotreated light	LD50, rabbit	> 2000 mg/kg

Inhalation: Based on available data, the classification criteria are not met.

Substance	Test	Result
Distillates (petroleum), hydrotreated light	LC50, rat, 4 hours	> 5.2 mg/l

Skin corrosion/irritation: Prolonged or repeated skin contact may defat the skin and cause skin irritation.

Substance	Test	Result
Distillates (petroleum), hydrotreated light	Skin irritation, rabbit	Slightly irritating / Moderately irritating

Serious eye damage/irritation: Direct contact may cause mild eye irritation. Based on available data, the classification criteria are not met.

Substance	Test	Result
Distillates (petroleum), hydrotreated light	Eye irritation, rabbit	Not irritating /Slightly irritating

Respiratory or skin sensitisation: Not expected to cause sensitization.

Substance	Test	Result
Distillates (petroleum), hydrotreated light	Skin sensitization, guinea pig	Not sensitizing

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: As per 29 CFR 1910.1200 (Hazard Communication), this product contains no carcinogens as listed by the National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC), the Occupational Safety and Health Administration (OSHA) or Regulation (EC) No 1272/2008.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: May cause drowsiness or dizziness.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: May be fatal if swallowed and enters airways.

Other information: None

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. The information given below is based on a knowledge of the components and the ecotoxicology of similar substances.

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Expected to biodegrade relatively quickly; can degrade rapidly in air. This substance is expected to be removed in a wastewater treatment facility. OECD 301F, 28 days: inherently biodegradable.

12.3. Bioaccumulative potential

Octanol/water partition coefficient (log Kow): 2.1-6.5.

12.4. Mobility in soil

Liquid. Insoluble in water. In determining environmental mobility, consider the product's physical and chemical properties (see Section 9). The hazardous ingredients will rapidly evaporate to the air if released into the water.

12.5. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS**13.1. Waste treatment methods**

Incinerate absorbed material with a properly licensed facility. Spent solvent is amenable to incineration or fuel blending. Check local, state and national/federal regulations and comply with the most stringent requirement. This product is classified as a hazardous waste according to 2008/98/EC.

SECTION 14: TRANSPORT INFORMATION**14.1. UN number**

ADR/RID/ADN/IMDG/ICAO: UN3082
TDG: UN3082
US DOT: UN3082

14.2. UN proper shipping name

ADR/RID/ADN/IMDG/ICAO: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (DISTILLATES, (PETROLEUM) HYDROTREATED LIGHT)
TDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (DISTILLATES, (PETROLEUM) HYDROTREATED LIGHT)
US DOT: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (DISTILLATES, (PETROLEUM) HYDROTREATED LIGHT)

14.3. Transport hazard class(es)

ADR/RID/ADN/IMDG/ICAO: 9
TDG: 9
US DOT: 9

14.4. Packing group

ADR/RID/ADN/IMDG/ICAO: III
TDG: III
US DOT: III

14.5. Environmental hazards

MARINE POLLUTANT

14.6. Special precautions for user

NO SPECIAL PRECAUTIONS FOR USER

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

NOT APPLICABLE

14.8. Other information

US DOT: ERG NO.171,

May be shipped as NON-RESTRICTED in non-bulk packagings (119 gallons or less) by motor vehicle, rail car or aircraft.
 (49 CFR 171.4(c))

IMDG: EmS. F-A, S-F

May be shipped as NON-RESTRICTED in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less. (IMDG CODE Amendment 37-14, 2.10.2.7)

ICAO/IATA: May be shipped as NON-RESTRICTED in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less. (IATA Dangerous Goods Regulation 56th edition, 4.4 Special Provisions A197)

ADR: Classification code M6 Tunnel restriction code (E)

May be shipped as NON-RESTRICTED in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less. (ADR 2015 Volume 1, Chapter 3.3 Special Provisions 375)

SECTION 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.1. National regulations****US EPA SARA TITLE III****312 Hazards:**

Immediate
 Fire

313 Chemicals:

None

TSCA: All chemical components are listed in the TSCA inventory.

Other national regulations: National implementation of the EC Directive referred to in section 15.1.1.

SECTION 16: OTHER INFORMATION

Abbreviations and acronyms: ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE: Acute Toxicity Estimate
 BCF: Bioconcentration Factor
 cATpE: Converted Acute Toxicity point Estimate
 ES: Exposure Standard
 GHS: Globally Harmonized System
 ICAO: International Civil Aviation Organization
 IMDG: International Maritime Dangerous Goods
 LC50: Lethal Concentration to 50 % of a test population
 LD50: Lethal Dose to 50% of a test population
 LOEL: Lowest Observed Effect Level
 N/A: Not Applicable
 NA: Not Available
 NOEC: No Observed Effect Concentration
 NOEL: No Observed Effect Level
 OECD: Organization for Economic Co-operation and Development
 (Q)SAR: Quantitative Structure-Activity Relationship
 REL: Recommended Exposure Limit
 RID: Regulations concerning the International Carriage of Dangerous Goods by Rail
 SDS: Safety Data Sheet
 STEL: Short Term Exposure Limit
 STOT RE: Specific Target Organ Toxicity, Repeated Exposure
 STOT SE: Specific Target Organ Toxicity, Single Exposure
 TDG: Transportation of Dangerous Goods (Canada)
 TWA: Time Weighted Average
 US DOT: United States Department of Transportation
 WHMIS: Workplace Hazardous Materials Information System
 Other abbreviations and acronyms can be looked up at www.wikipedia.org.

Key literature references and sources for data: Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST)
 Chemical Classification and Information Database (CCID)
 European Chemicals Agency (ECHA) - Information on Chemicals
 Hazardous Chemical Information System (HCIS)
 National Institute of Technology and Evaluation (NITE)
 U.S. National Library of Medicine Toxicology Data Network (TOXNET)

Relevant H-statements: H227: Combustible liquid.
 H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H336: May cause drowsiness or dizziness.
 H411: Toxic to aquatic life with long lasting effects.

Hazard pictogram names: Health hazard, exclamation mark, environment.

Changes to the SDS in this revision: Section 2.1.

Revision date: 24 September 2020

Further information: None

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself. No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose. The user must make their own determination as to suitability.