



SAFETY DATA SHEET

in accordance with 2015/830/EU (REACH, Annex II) 29 CFR 1910.1200, WHMIS 2015 and Safe Work Australia

Revision date: 16 December 2019

Initial date of issue: 5 July 2007

SDS No. 181A-21

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

395 Tapping Lubricant (Aerosol)

1.2. Relevant identified uses of the substance or mixture and uses advised against

A high-quality petroleum based lubricant specifically designed for Aluminum and other soft metals.

1.3. Details of the supplier of the safety data sheet

Company:

A.W. CHESTERTON COMPANY
860 Salem Street
Groveland, MA 01834-1507, USA
Tel. +1 978-469-6446 Fax: +1 978-469-6785
(Mon. - Fri. 8:30 - 5:00 PM EST)
SDS requests: www.chesterton.com
E-mail (SDS questions): ProductSDSs@chesterton.com
E-mail: customer.service@chesterton.com

Supplier:

Canada: A.W. Chesterton Company Ltd., 889 Fraser Drive,
Unit 105, Burlington, Ontario L7L 4X8 – Tel. 905-335-5055
EU: Chesterton International GmbH, Am Lenzenfleck 23,
D85737 Ismaning, Germany – Tel. +49-89-996-5460

1.4. Emergency telephone number

24 hours per day, 7 days per week
Call Infotrac: 1-800-535-5053
Outside N. America: +1 352-323-3500 (collect)
NSW Poisons Information Centre (Australia): 13 11 26

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

2.1.1. Classification according to Regulation (EC) No 1272/2008 [CLP]

Aerosol, Category 1, H222, H229
Aspiration hazard, Category 1, H304*
Specific target organ toxicity – single exposure, Category 3, H336
Hazardous to the aquatic environment, Chronic, Category 3, H412

*Labelling not required for aerosols containing substances or mixtures classified as presenting an aspiration hazard, under Article 23 of the CLP.

2.1.2. Classification according to 29 CFR 1910.1200 / WHMIS 2015

Flammable aerosol, Category 1, H222
Gases under pressure (Compressed gas), H280
Aspiration hazard, Category 1, H304
Skin irritation, Category 3, H316
Specific target organ toxicity – single exposure, Category 3, H336
Hazardous to the aquatic environment, Chronic, Category 3, H412

2.1.3. Australian statement of hazardous nature

Hazardous according to criteria of Safe Work Australia.

2.1.4. Additional information

For full text of H-statements: see SECTIONS 2.2 and 16.

2.2. Label elements**2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]****Hazard pictograms:****Signal word:**

Danger

Hazard statements:

H222 Extremely flammable aerosol.
 H229 Pressurized container: May burst if heated.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing vapours/spray.
 P273 Avoid release to the environment.
 P312 Call a POISON CENTER or doctor if you feel unwell.
 P410/412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Supplemental information: None**2.2.2. Labelling according to 29 CFR 1910.1200 / WHMIS 2015****Hazard pictograms:****Signal word:**

Danger

Hazard statements:

H222 Extremely flammable aerosol.
 H280 Contains gas under pressure; may explode if heated.
 H304 May be fatal if swallowed and enters airways.
 H316 Causes mild skin irritation.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor.
 P331 Do NOT induce vomiting.
 P304/340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTER or doctor if you feel unwell.
 P332/313 If skin irritation occurs: Get medical advice/attention.
 P403 Store in a well-ventilated place.
 P410/412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container to an approved waste disposal plant.

Supplemental information: None**2.3. Other hazards**

None known

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures**

Hazardous Ingredients ¹	% Wt.	CAS No./ EC No.	REACH Reg. No.	CLP/GHS Classification
Distillates (petroleum), hydrotreated light	50-60	64742-47-8 265-149-8	NA	Flam. Liq. 4, H227* Asp. Tox. 1, H304 Skin Irrit. 3, H316* STOT SE 3, H336 Aquatic Chronic 3, H412
Propane	5-10	74-98-6 200-827-9	NA	Flam. Gas 1, H220 Press. Gas (Comp.), H280 Simple Asphyxiant (US/Can.)

Other ingredients:

White mineral oil (petroleum)	25-35	8042-47-5 232-455-8	NA	Not classified**
-------------------------------	-------	------------------------	----	------------------

*Non-CLP classification.

**Substance with a workplace exposure limit.

For full text of H-statements: see SECTION 16.

¹ Classified according to:

- 29 CFR 1910.1200, 1915, 1916, 1917, Mass. Right-to-Know Law (ch. 40, M.G.L..O. 111F)
- 1272/2008/EC, GHS, REACH
- WHMIS 2015
- Safe Work Australia

SECTION 4: FIRST AID MEASURES**4.1. Description of first aid measures****Inhalation:** Remove to fresh air. If not breathing, administer artificial respiration. Contact physician immediately.**Skin contact:** Wash skin with soap and water. Contact physician if irritation persists.**Eye contact:** Flush eyes for at least 15 minutes with large amounts of water. Contact physician if irritation persists.**Ingestion:** Do not induce vomiting. Contact physician immediately.**Protection of first-aiders:** No action shall be taken involving any personal risk or without suitable training. Avoid contact with the product while providing aid to the victim. Avoid breathing vapors. See section 8.2.2 for recommendations on personal protective equipment.**4.2. Most important symptoms and effects, both acute and delayed**

Vapor in high concentrations may irritate the respiratory tract and cause drowsiness, unconsciousness, headache, dizziness and other central nervous system effects. Repeated exposure may cause skin dryness or cracking. Aspiration into the lungs may cause chemical pneumonitis or pulmonary oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: FIREFIGHTING MEASURES**5.1. Extinguishing media****Suitable extinguishing media:** Carbon dioxide, dry chemical, foam or water spray.**Unsuitable extinguishing media:** Water jets**5.2. Special hazards arising from the substance or mixture**

Pressurized containers, when heated, are a potential explosive hazard. Hazardous combustion products: Carbon Monoxide, Carbon Dioxide and other toxic fumes.

5.3. Advice for firefighters

Cool exposed containers with water. Recommend Firefighters wear self-contained breathing apparatus.

Flammability Classification: –**HAZCHEM Emergency Action Code:** 22 Y

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Provide adequate ventilation. Utilize exposure controls and personal protection as specified in Section 8.

6.2. Environmental Precautions

Keep out of sewers, streams and waterways.

6.3. Methods and material for containment and cleaning up

Contain spill to a small area. Keep away from sources of ignition - No smoking. If removal of ignition sources is not possible, then flush material away with water. Pick up with absorbent material (sand, sawdust, clay, etc.) and place in a suitable container for disposal.

6.4. Reference to other sections

Refer to section 13 for disposal advice.

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling**

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No Smoking. Vapors are heavier than air and will collect in low areas. Vapor accumulations could flash and/or explode if ignited. Observe good work practice - avoid eating, drinking and smoking in the work area while using any hydrocarbons.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C (120°F). Do not pierce or burn, even after use.

7.3. Specific end use(s)

No special precautions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limit values**

Ingredients	OSHA PEL ¹		ACGIH TLV ²		UK WEL ³		AUSTRALIA ES ⁴	
	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Distillates (petroleum), hydrotreated light	N/A	N/A	179*	1200*	N/A	N/A	N/A	N/A
Propane	1,000	1,800	N/A **	N/A	N/A	N/A	N/A **	N/A
Oil mist, mineral	N/A	5	N/A	5	N/A	N/A	N/A	5

* Based on the procedure described in appendix H, "Reciprocal calculation method for Certain Refined Hydrocarbon Solvent Vapor Mixtures" of the ACGIH TLVs® and BEIs®.

** Simple asphyxiant.

¹ United States Occupational Health & Safety Administration permissible exposure limits

² American Conference of Governmental Industrial Hygienists threshold limit values

³ EH40 Workplace exposure limits, Health & Safety Executive

⁴ Safe Work Australia, Workplace Exposure Standards for Airborne Contaminants

Biological limit values

Not available

Derived No Effect Level (DNEL) according to Regulation (EC) No 1907/2006:**Workers**

Substance	Route of exposure	Potential health effects	DNEL
White mineral oil (petroleum)	Inhalation	Chronic effects, systemic	160 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No 1907/2006: Predicted No Effect Concentration (PNEC) according to Regulation (EC) No 1907/2006:

Not available

8.2. Exposure controls**8.2.1. Engineering measures**

Use only in well-ventilated areas. If exposure limits are exceeded, provide adequate ventilation.

8.2.2. Individual protection measures

Respiratory protection: Not normally needed. If exposure limits are exceeded, use a half or full-face respirator with combined dust/organic vapour filter (EN filter type A-P2).

Protective gloves: Chemical resistant gloves (e.g. Viton*, neoprene, nitrile). *DuPont's registered trademark.

Eye and face protection: Safety glasses

Other: None

8.2.3. Environmental exposure controls

Refer to sections 6 and 12.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Physical state	low viscosity liquid	Odour	mild
Colour	clear yellow	Odour threshold	not determined
Initial boiling point	182°C (360°F), product only	Vapour pressure @ 20°C	not determined
Melting point	not determined	% Aromatics by weight	0.6%, product only
% Volatile (by volume)	65.7%	pH	not applicable
Flash point	71°C (160°F), product only	Relative density	0.83 kg/l, product only
Method	PM Closed Cup	Weight per volume	6.9 lbs/gal, product only
Viscosity	not determined	Coefficient (water/oil)	< 1
Autoignition temperature	> 200°C (> 392°F), product only	Vapour density (air=1)	> 1
Decomposition temperature	not determined	Rate of evaporation (ether=1)	< 1
Upper/lower flammability or explosive limits	not determined	Solubility in water	negligible
Flammability (solid, gas)	extremely flammable (propellant)	Oxidising properties	not determined
Explosive properties	not determined		

9.2. Other information

Kinematic viscosity at 40°C: 4.2 cSt (product only).

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

Refer to sections 10.3 and 10.5.

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No dangerous reactions known under conditions of normal use. No dangerous reactions known under conditions of normal use.

10.4. Conditions to avoid

Open flames, heat, sparks and red hot surfaces.

10.5. Incompatible materials

Strong oxidizers like liquid Chlorine and concentrated Oxygen.

10.6. Hazardous decomposition products

Carbon Monoxide, Carbon Dioxide and other toxic fumes.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects****Primary route of exposure under normal use:** Inhalation, skin and eye contact.**Acute toxicity -****Oral:**

Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Distillates (petroleum), hydrotreated light	LD50, oral, rat	> 5,000 mg/kg
White mineral oil (petroleum)	LD50, oral	> 5,000 mg/kg

Dermal:

Substance	Test	Result
Distillates (petroleum), hydrotreated light	LD50 dermal, rabbit	> 2,000 mg/kg
White mineral oil (petroleum)	LD50, rabbit	> 2,000 mg/kg

Inhalation:

Vapor in high concentrations may irritate the respiratory tract and cause drowsiness, unconsciousness, headache, dizziness and other central nervous system effects.

Substance	Test	Result
Distillates (petroleum), hydrotreated light	LC50 inhalation, rat, 4 h	> 5.28 mg/l
Propane	LC50 inhalation, rat, 4 h	658 mg/l
White mineral oil (petroleum)	LC50 inhalation, rat, 4 h	> 5 mg/l (mist)

Skin corrosion/irritation:

Repeated exposure may cause skin dryness or cracking.

Substance	Test	Result
Distillates (petroleum), hydrotreated light	Skin irritation, rabbit	Slightly irritating / Moderately irritating
White mineral oil (petroleum)	Skin irritation, rabbit	Not irritating

Serious eye damage/irritation:

Substance	Test	Result
Distillates (petroleum), hydrotreated light	Eye irritation, rabbit	Not irritating / Slightly irritating
White mineral oil (petroleum)	Eye irritation	Not irritating

Respiratory or skin sensitisation:

Substance	Test	Result
Distillates (petroleum), hydrotreated light	Skin sensitization, guinea pig	Not sensitizing
White mineral oil (petroleum)	Skin sensitization, guinea pig	Not sensitizing

Germ cell mutagenicity:

White mineral oil (petroleum), Distillates (petroleum), hydrotreated light: not expected to be a germ cell mutagen.

Carcinogenicity:

This product contains no carcinogens as listed by the National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC), the Occupational Safety and Health Administration (OSHA) or the European Chemicals Agency (ECHA).

Reproductive toxicity:

White mineral oil (petroleum), Distillates (petroleum), hydrotreated light: based on available data, the classification criteria are not met.

STOT – single exposure:

May cause drowsiness or dizziness.

STOT – repeated exposure:

Not expected to cause toxicity.

Aspiration hazard:

Aspiration into the lungs may cause chemical pneumonitis or pulmonary oedema.

Other information:

None known

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. The information given below is based on a knowledge of the components and the ecotoxicology of similar substances.

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Distillates (petroleum), hydrotreated light, Propane: expected to degrade rapidly in air. Distillates (petroleum), hydrotreated light: expected to biodegrade relatively quickly. Mineral oil: not readily biodegradable.

12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated light, Octanol/water partition coefficient (log Kow): 2.1 – 5. Propane: not expected to bioaccumulate. White mineral oil (petroleum), Octanol/water partition coefficient (log Pow): > 6.

12.4. Mobility in soil

Liquid. Insoluble in water. Floats on water. Surface tension < 33 mN/m @ 25°C, product only. The hazardous ingredients will rapidly evaporate to the air if released into the environment.

12.5. Results of PBT and vPvB assessment

Not available

12.6. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS**13.1. Waste treatment methods**

Incinerate absorbed material with a properly licensed facility. Incinerate pressurized or sealed containers in an approved facility. Check local, state and national/federal regulations and comply with the most stringent requirement. This product is classified as a hazardous waste according to 2008/98/EC.

SECTION 14: TRANSPORT INFORMATION**14.1. UN number**

ADG/ADR/RID/ADN/IMDG/ICAO:	UN1950
TDG:	UN1950
US DOT:	UN1950

14.2. UN proper shipping name

ICAO:	Aerosols, Flammable
ADG/IMDG:	Aerosols
ADR/RID/ADN:	Aerosols, <i>flammable</i>
TDG:	Aerosols, <i>flammable</i>
US DOT:	Aerosols, <i>flammable</i>

14.3. Transport hazard class(es)

ADG/ADR/RID/ADN/IMDG/ICAO:	2.1
TDG:	2.1
US DOT:	2.1

14.4. Packing group

ADG/ADR/RID/ADN/IMDG/ICAO:	NOT APPLICABLE
TDG:	NOT APPLICABLE
US DOT:	NOT APPLICABLE

14.5. Environmental hazards

NO ENVIRONMENTAL HAZARDS

14.6. Special precautions for user

NO SPECIAL PRECAUTIONS FOR USER

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

NOT APPLICABLE

14.8. Other information

US DOT: Shipped as Limited Quantity in packaging having a rated capacity gross weight of 66 lb. or less (49 CFR 173.306(a),(3),(i)).
ERG NO. 126

IMDG: EmS. F-D, S-U, Shipped as Limited Quantity

ADR: Classification code 5F, Tunnel restriction code (E), Shipped as Limited Quantity

ADG HAZCHEM CODE: N/A **HIN:** (1)

SECTION 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.1. EU regulations**

Authorisations under Title VII: Not applicable

Restrictions under Title VIII: None

Other EU regulations: Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers.
Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances (hazard category P3a, Flammable Aerosols; qualifying quantities: 150 t (net), 500 t (net)).

15.1.2. National regulations**US EPA SARA TITLE III****312 Hazards:**

Flammable aerosol
Gases under pressure
Aspiration hazard
Specific target organ toxicity – single exposure

313 Chemicals:

None

Other national regulations: National implementations of the EC Directives referred to in section 15.1.1.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION

Abbreviations and acronyms: ADG: Australian Dangerous Goods Code
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE: Acute Toxicity Estimate
BCF: Bioconcentration Factor
cATpE: Converted Acute Toxicity point Estimate
CLP: Classification Labelling Packaging Regulation (1272/2008/EC)
ES: Exposure Standard
GHS: Globally Harmonized System
ICAO: International Civil Aviation Organization
IMDG: International Maritime Dangerous Goods
LC50: Lethal Concentration to 50 % of a test population
LD50: Lethal Dose to 50% of a test population
LOEL: Lowest Observed Effect Level
N/A: Not Applicable
NA: Not Available
NOEC: No Observed Effect Concentration
NOEL: No Observed Effect Level
OECD: Organization for Economic Co-operation and Development
PBT: Persistent, Bioaccumulative and Toxic substance
(Q)SAR: Quantitative Structure-Activity Relationship
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (1907/2006/EC)
REL: Recommended Exposure Limit
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS: Safety Data Sheet
STEL: Short Term Exposure Limit
STOT RE: Specific Target Organ Toxicity, Repeated Exposure
STOT SE: Specific Target Organ Toxicity, Single Exposure
TDG: Transportation of Dangerous Goods (Canada)
TWA: Time Weighted Average
US DOT: United States Department of Transportation
vPvB: very Persistent and very Bioaccumulative substance
WEL: Workplace Exposure Limit
WHMIS: Workplace Hazardous Materials Information System
Other abbreviations and acronyms can be looked up at www.wikipedia.org.

Key literature references and sources for data: Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST)
 Chemical Classification and Information Database (CCID)
 European Chemicals Agency (ECHA) - Information on Chemicals
 Hazardous Chemical Information System (HCIS)
 National Institute of Technology and Evaluation (NITE)
 Swedish Chemicals Agency (KEMI)
 U.S. National Library of Medicine Toxicology Data Network (TOXNET)

Procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008 [CLP]:

Classification	Classification procedure
Aerosol 1, H222, H229	On basis of components and packaging
Asp. Tox. 1, H304	On basis of components and test data
STOT SE 3, H336	Bridging principle "Dilution"
Aquatic Chronic 3, H412	Calculation method

Relevant H-statements: H220: Extremely flammable gas.
 H227: Combustible liquid.
 H229: Pressurized container: May burst if heated.
 H280: Contains gas under pressure; may explode if heated.
 H304: May be fatal if swallowed and enters airways.
 H316 : Causes mild skin irritation.
 H336: May cause drowsiness or dizziness.
 H412: Harmful to aquatic life with long lasting effects.

Hazard pictogram names: Flame, gas cylinder *, health hazard *, exclamation mark
 * Non-CLP label.

Further information: None

Date of last revision: 16 December 2019

Changes to the SDS in this revision: Sections 1.3, 2.1, 2.2, 3, 4.1, 4.2, 7.1, 8.1, 9.1, 11, 12.5, 15.1, 16.

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself. No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose. The user must make their own determination as to suitability.