



SAFETY DATA SHEET

in accordance with 2015/830/EU (REACH, Annex II) 29 CFR 1910.1200, WHMIS 2015 and Safe Work Australia

Revision date: 20 December 2019

Initial date of issue: 16 May 2008

SDS No. 170A-18

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

660 Silicone Lubricant (Aerosol)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Synthetic Base Lubricant. General purpose, continuous film lubricant for mechanical parts and sliding surfaces constructed of plastic, rubber or metal.

1.3. Details of the supplier of the safety data sheet

Company:

A.W. CHESTERTON COMPANY
860 Salem Street
Groveland, MA 01834-1507, USA
Tel. +1 978-469-6446 Fax: +1 978-469-6785
(Mon. - Fri. 8:30 - 5:00 PM EST)
SDS requests: www.chesterton.com
E-mail (SDS questions): ProductSDSs@chesterton.com
E-mail: customer.service@chesterton.com

Supplier:

Canada: A.W. Chesterton Company Ltd., 889 Fraser Drive,
Unit 105, Burlington, Ontario L7L 4X8 – Tel. 905-335-5055
EU: Chesterton International GmbH, Am Lenzenfleck 23,
D85737 Ismaning, Germany – Tel. +49-89-996-5460

1.4. Emergency telephone number

24 hours per day, 7 days per week
Call Infotrac: 1-800-535-5053
Outside N. America: +1 352-323-3500 (collect)
NSW Poisons Information Centre (Australia): 13 11 26

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

2.1.1. Classification according to Regulation (EC) No 1272/2008 [CLP]

Aerosol, Category 1, H222, H229
Skin irritation, Category 2, H315
Specific target organ toxicity – single exposure, Category 3, H336
Hazardous to the aquatic environment, Chronic, Category 2, H411

2.1.2. Classification according to 29 CFR 1910.1200 / WHMIS 2015

Flammable aerosol, Category 1, H222
Compressed gas, H280
Skin irritation, Category 2, H315
Specific target organ toxicity – single exposure, Category 3, H336
Hazardous to the aquatic environment, Chronic, Category 2, H411

2.1.3. Australian statement of hazardous nature

Hazardous according to criteria of Safe Work Australia.

2.1.4. Additional information

For full text of H-statements: see SECTIONS 2.2 and 16.

2.2. Label elements**2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]****Hazard pictograms:****Signal word:**

Danger

Hazard statements:

H222 Extremely flammable aerosol.
 H229 Pressurized container: May burst if heated.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing vapours/spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves and eye protection.
 P302/352 IF ON SKIN: Wash with plenty of soap and water.
 P312 Call a POISON CENTER or doctor if you feel unwell.
 P410/412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Supplemental information: None**2.2.2. Labelling according to 29 CFR 1910.1200 / WHMIS 2015****Hazard pictograms:****Signal word:**

Danger

Hazard statements:

H222 Extremely flammable aerosol.
 H280 Contains gas under pressure; may explode if heated.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P260 Do not breathe vapours/spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves and eye protection.
 P302/352 IF ON SKIN: Wash with plenty of soap and water.
 P304/340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTER or doctor if you feel unwell.
 P332/313 If skin irritation occurs: Get medical advice/attention.
 P362/364 Take off contaminated clothing and wash it before reuse.
 P403 Store in a well-ventilated place.
 P410/412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container to an approved waste disposal plant.

Supplemental information: None**2.3. Other hazards**

None known

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures**

Hazardous Ingredients ¹	% Wt.	CAS No./ EC No.	REACH Reg. No.	CLP/GHS Classification
Naphtha (petroleum), light alkylate*	50-60	64741-66-8 265-068-8	NA	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411
Propane	30-40	74-98-6 200-827-9	NA	Flam. Gas 1, H220 Press. Gas (Comp.), H280 Simple Asphyxiant (US/Can.)
Isobutane**	1-5	75-28-5 200-857-2	NA	Flam. Gas 1, H220 Press. Gas (Comp.), H280 Simple Asphyxiant (US/Can.)

For full text of H-statements: see SECTION 16.

*Contains less than 0.1 % w/w Benzene. **Contains less than 0.1 % w/w 1,3-Butadiene.

¹ Classified according to: • 29 CFR 1910.1200, 1915, 1916, 1917, Mass. Right-to-Know Law (ch. 40, M.G.L..O. 111F)
• 1272/2008/EC, GHS, REACH
• WHMIS 2015
• Safe Work Australia

SECTION 4: FIRST AID MEASURES**4.1. Description of first aid measures**

Inhalation: Remove to fresh air. If not breathing, administer artificial respiration. Contact physician immediately.

Skin contact: Wash skin with soap and water. Take off contaminated clothing and wash it before reuse. Contact physician if irritation persists.

Eye contact: Flush eyes for at least 15 minutes with large amounts of water. Contact physician if irritation persists.

Ingestion: Do not induce vomiting. If conscious, drink large quantities of water. Contact physician immediately.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. Avoid contact with skin. Avoid breathing vapors. See section 8.2.2 for recommendations on personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation. Direct contact may cause mild eye irritation. Inhalation of vapor concentrations in excess of 1000 ppm will cause eye and respiratory tract irritation, dizziness, headache and other central nervous system effects.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: FIREFIGHTING MEASURES**5.1. Extinguishing media**

Suitable extinguishing media: Carbon dioxide, dry chemical or foam

Unsuitable extinguishing media: High volume water jet

5.2. Special hazards arising from the substance or mixture

Pressurized containers, when heated, are a potential explosive hazard.

5.3. Advice for firefighters

Cool exposed containers with water. Recommend Firefighters wear self-contained breathing apparatus.

Flammability Classification: –

HAZCHEM Emergency Action Code: 3 Y

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Provide adequate ventilation. Utilize exposure controls and personal protection as specified in Section 8.

6.2. Environmental Precautions

Keep out of sewers, streams and waterways.

6.3. Methods and material for containment and cleaning up

Contain spill to a small area. Keep away from sources of ignition - No smoking. If removal of ignition sources is not possible, then flush material away with water. Pick up with absorbent material (sand, sawdust, clay, etc.) and place in a suitable container for disposal.

6.4. Reference to other sections

Refer to section 13 for disposal advice.

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling**

Vapors are heavier than air and will collect in low areas. Vapor accumulations could flash and/or explode if ignited. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No Smoking. Wash skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C (120°F). Do not pierce or burn, even after use. Store in a well-ventilated place.

7.3. Specific end use(s)

No special precautions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limit values**

Ingredients	OSHA PEL ¹		ACGIH TLV ²		UK WEL ³		AUSTRALIA ES ⁴	
	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Naphtha (petroleum), light alkylate*	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Propane	1000	1800	**	N/A	N/A	N/A	**	N/A
Isobutane	N/A	N/A	STEL: 1000	N/A	N/A	N/A	N/A	N/A

*Chesterton recommended limit: 241 ppm (1200 mg/m³). **Simple asphyxiant.

¹ United States Occupational Health & Safety Administration permissible exposure limits

² American Conference of Governmental Industrial Hygienists threshold limit values

³ EH40 Workplace exposure limits, Health & Safety Executive

⁴ Safe Work Australia, Workplace Exposure Standards for Airborne Contaminants

Biological limit values

Not available

Derived No Effect Level (DNEL) according to Regulation (EC) No 1907/2006:**Workers**

Substance	Route of exposure	Potential health effects	DNEL
Hydrocarbons, C7-C9, isoalkanes	Inhalation	Chronic effects, systemic	2035 mg/m ³
	Dermal	Chronic effects, systemic	773 mg/kg/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No 1907/2006:

Not available

8.2. Exposure controls**8.2.1. Engineering measures**

Provide sufficient ventilation to keep the vapor concentrations below the exposure limits.

8.2.2. Individual protection measures

Respiratory protection: Not normally needed. If exposure limits are exceeded, use approved organic vapor respirator (e.g., EN filter type A-P).

Protective gloves: Chemical resistant gloves (e.g. neoprene, nitrile).

Eye and face protection: Safety goggles or glasses.

Other: Impervious clothing as necessary for repetitive, prolonged skin contact.

8.2.3. Environmental exposure controls

Refer to sections 6 and 12.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Physical state	liquid	Odour	mild odor
Colour	clear	Odour threshold	not determined
Initial boiling point	116°C (240°F), product only	Vapour pressure @ 20°C	not determined
Melting point	not determined	% Aromatics by weight	0%
% Volatile (by volume)	93%, product only	pH	not applicable
Flash point	< 7°C (< 45°F)	Relative density	0.64 kg/l
Method	Tag Closed Cup, product only	Weight per volume	5.3 lbs/gal.
Viscosity	not determined	Coefficient (water/oil)	< 1
Autoignition temperature	not determined	Vapour density (air=1)	> 1
Decomposition temperature	not determined	Rate of evaporation (ether=1)	< 1
Upper/lower flammability or explosive limits	not determined	Solubility in water	insoluble
Flammability (solid, gas)	extremely flammable (propellant)	Oxidising properties	not determined
Explosive properties	not determined		

9.2. Other information

None

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

Refer to sections 10.3 and 10.5.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under conditions of normal use.

10.4. Conditions to avoid

Open flames and red hot surfaces.

10.5. Incompatible materials

Strong oxidizers like liquid Chlorine and concentrated Oxygen.

10.6. Hazardous decomposition products

Carbon Monoxide, aldehydes, oxides of Silicon and other toxic fumes.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

Primary route of exposure under normal use: Inhalation, skin and eye contact. Personnel with pre-existing dermatitis are generally aggravated by exposure.

Acute toxicity -

Oral: Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Naphtha (petroleum), light alkylate	LD50, rat	> 5000 mg/kg

Dermal: Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Naphtha (petroleum), light alkylate	LD50, rabbit	> 2000 mg/kg

Inhalation: Inhalation of vapor concentrations in excess of 1000 ppm will cause eye and respiratory tract irritation, dizziness, headache and other central nervous system effects.

Substance	Test	Result
Naphtha (petroleum), light alkylate	LC50, rat, 4 hours	> 2.1 mg/l (vapor)
Propane	LC50, rat 4 hours	658 mg/l
Isobutane	LC50, mouse, 1 h	52 mg/l

Skin corrosion/irritation: Moderate skin irritant.

Serious eye damage/irritation: May cause mild eye irritation.

Respiratory or skin sensitisation: Not expected to cause sensitization.

Germ cell mutagenicity: Naphtha (petroleum), light alkylate, Propane, Isobutane: not expected to be a germ cell mutagen.

Carcinogenicity: This product contains no carcinogens as listed by the National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC), the Occupational Safety and Health Administration (OSHA) or Regulation (EC) No 1272/2008.

Reproductive toxicity: Naphtha (petroleum), light alkylate, Propane, Isobutane: not expected to be a reproductive toxicant.

STOT – single exposure: May cause drowsiness or dizziness.

STOT – repeated exposure: Naphtha (petroleum), light alkylate, Propane, Isobutane: not expected to cause organ damage from prolonged or repeated exposure.

Aspiration hazard: Not classified as an aspiration toxicant due to the aerosol spray pattern.

Other information: None

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. The information given below is based on a knowledge of the components and the ecotoxicology of similar substances.

12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. 48 h EL50 (for daphnia): 2.4 mg/l (read-across). LOEC, 21 days, Daphnia: 0.32 mg/l (read-across).

12.2. Persistence and degradability

Naphtha (petroleum), light alkylate: expected to degrade rapidly in air; expected to be inherently biodegradable (biodegradability, 28 days: 22%). Naphtha (petroleum), light alkylate, Propane, Isobutane: oxidize by photochemical reactions in air.

12.3. Bioaccumulative potential

Propane, Isobutane: bioconcentration in aquatic organisms is not expected to be significant.

12.4. Mobility in soil

Liquid. Insoluble in water. In determining environmental mobility, consider the product's physical and chemical properties (see Section 9). The hazardous ingredients will rapidly evaporate to the air if released into the environment.

12.5. Results of PBT and vPvB assessment

Not available

12.6. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS**13.1. Waste treatment methods**

Incinerate absorbed material with a properly licensed facility. Incinerate pressurized or sealed containers in an approved facility. This product is classified as a hazardous waste according to 2008/98/EC. Check local, state and national/federal regulations and comply with the most stringent requirement.

SECTION 14: TRANSPORT INFORMATION**14.1. UN number**

ADG/ADR/RID/ADN/IMDG/ICAO: UN1950
TDG: UN1950
US DOT: UN1950

14.2. UN proper shipping name

ICAO: Aerosols, Flammable
ADG/IMDG: Aerosols
ADR/RID/ADN: Aerosols, *flammable*
TDG: Aerosols, *flammable*
US DOT: Aerosols, *flammable*

14.3. Transport hazard class(es)

ADG/ADR/RID/ADN/IMDG/ICAO: 2.1
TDG: 2.1
US DOT: 2.1

14.4. Packing group

ADG/ADR/RID/ADN/IMDG/ICAO: NOT APPLICABLE
TDG: NOT APPLICABLE
US DOT: NOT APPLICABLE

14.5. Environmental hazards

NO ENVIRONMENTAL HAZARDS

14.6. Special precautions for user

NO SPECIAL PRECAUTIONS FOR USER

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

NOT APPLICABLE

14.8. Other information

US DOT: Shipped as Limited Quantity in packaging having a rated capacity gross weight of 66 lb. or less (49 CFR 173.306(a),(3),(i)).
 ERG NO. 126
IMDG: EmS. F-D, S-U, Shipped as Limited Quantity
ADR: Classification code 5F, Tunnel restriction code (E), Shipped as Limited Quantity
ADG HAZCHEM CODE: N/A **HIN:** (1)

SECTION 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.1. EU regulations**

Authorisations under Title VII: Not applicable

Restrictions under Title VIII: None

Other EU regulations: Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers.
 Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances (hazard category P3a, Flammable Aerosols; qualifying quantities: 150 t (net), 500 t (net)).

15.1.2. National regulations**US EPA SARA TITLE III****312 Hazards:**

Flammable aerosol
 Gases under pressure
 Skin irritation
 Specific target organ toxicity – single exposure

313 Chemicals:

None

Other national regulations: National implementation of the EC Directive referred to in section 15.1.1.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION

Abbreviations and acronyms: ADG: Australian Dangerous Goods Code
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE: Acute Toxicity Estimate
 BCF: Bioconcentration Factor
 cATpE: Converted Acute Toxicity point Estimate
 CLP: Classification Labelling Packaging Regulation (1272/2008/EC)
 ES: Exposure Standard
 GHS: Globally Harmonized System
 ICAO: International Civil Aviation Organization
 IMDG: International Maritime Dangerous Goods
 LC50: Lethal Concentration to 50 % of a test population
 LD50: Lethal Dose to 50% of a test population
 LOEL: Lowest Observed Effect Level
 N/A: Not Applicable
 NA: Not Available
 NOEC: No Observed Effect Concentration
 NOEL: No Observed Effect Level
 OECD: Organization for Economic Co-operation and Development
 PBT: Persistent, Bioaccumulative and Toxic substance
 (Q)SAR: Quantitative Structure-Activity Relationship
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (1907/2006/EC)
 REL: Recommended Exposure Limit
 RID: Regulations concerning the International Carriage of Dangerous Goods by Rail
 SDS: Safety Data Sheet
 STEL: Short Term Exposure Limit
 STOT RE: Specific Target Organ Toxicity, Repeated Exposure
 STOT SE: Specific Target Organ Toxicity, Single Exposure
 TDG: Transportation of Dangerous Goods (Canada)
 TWA: Time Weighted Average
 US DOT: United States Department of Transportation
 vPvB: very Persistent and very Bioaccumulative substance
 WEL: Workplace Exposure Limit
 WHMIS: Workplace Hazardous Materials Information System
 Other abbreviations and acronyms can be looked up at www.wikipedia.org.

Key literature references and sources for data: Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST)
 Chemical Classification and Information Database (CCID)
 European Chemicals Agency (ECHA) - Information on Chemicals
 Hazardous Chemical Information System (HCIS)
 National Institute of Technology and Evaluation (NITE)
 Swedish Chemicals Agency (KEMI)
 U.S. National Library of Medicine Toxicology Data Network (TOXNET)

Procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008 [CLP]:

Classification	Classification procedure
Aerosol 1, H222, H229	On basis of components and packaging
Skin Irrit. 2, H315	Calculation method
STOT SE 3, H336	Bridging principle "Dilution"
Aquatic Chronic 2, H411	Calculation method

Relevant H-statements: H220: Extremely flammable gas.
 H225: Highly flammable liquid and vapour.
 H280: Contains gas under pressure; may explode if heated.
 H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H336: May cause drowsiness or dizziness.
 H411: Toxic to aquatic life with long lasting effects.

Hazard pictogram names: Flame, gas cylinder (non-CLP labelling) exclamation mark, environment

Further information: None

Date of last revision: 20 December 2019

Changes to the SDS in this revision: Sections 2.1, 3, 4.1, 8.1, 9.1, 11, 12.2, 12.3, 15.1, 16.

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself. No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose. The user must make their own determination as to suitability.